

# Deck-Based Wide Block Cipher Modes

Aldo Gunsing, Joan Daemen and Bart Mennink

Digital Security Group, Radboud University, Nijmegen, The Netherlands

[aldo.gunsing@ru.nl](mailto:aldo.gunsing@ru.nl), [joan@cs.ru.nl](mailto:joan@cs.ru.nl), [b.mennink@cs.ru.nl](mailto:b.mennink@cs.ru.nl)

**Abstract.** We present two tweakable wide block cipher modes from doubly-extendable cryptographic keyed (deck) functions and a keyed hash function: double-decker and docked-double-decker. Double-decker is a direct generalization of Farfalle-WBC of Bertoni et al. (ToSC 2017(4)), and is a four-round Feistel network on two arbitrarily large branches, where the middle two rounds call deck functions and the first and last rounds call the keyed hash function. Docked-double-decker is a variant of double-decker where the bulk of the input to the deck functions is moved to the keyed hash functions. As a consequence, the size of the inputs of the deck functions are constant and can be conceptually seen as stream ciphers. Concretely, docked-double-decker can be instantiated using the same primitives as Adiantum, without using any block cipher, arguably having a slightly more efficient design and being more secure in certain settings.

**Keywords:** wide block cipher · tweakable · deck function · double-decker · docked-double-decker · disk encryption · incremental tweak

## 1 Introduction

Block ciphers have long been the main building block for symmetric cryptography. However, block ciphers operate on data of fixed and predetermined length. For example, DES had a block size of 64 bits and AES has a block size of 128 bits. One can encrypt data of variable length by using a block cipher in a mode of operation, such as counter mode, CBC or OFB.

Security of such modes typically depends on a nonce. This might be a random value that should never be repeated or a counter. In some applications it is desirable to have security even in the absence of a nonce or in the case of accidental nonce violation. For example, with full disk encryption the nonce serves as the sector index. When the content of a sector changes, this is re-encrypted with the same sector index as nonce. Consider an adversary that may have access to the encrypted sector before and after the change. In the case of stream encryption it can derive from this the bitwise difference of the plaintexts:  $P \oplus P' = C \oplus C'$ . When CBC would be used, it still leaks equality of first blocks. A solution would be to store a counter in the sector that would increment with each re-encryption, but often it is undesirable to have a difference between the sector size with or without encryption. Another example is the Tor protocol for anonymity. It enciphers the payload in network packets iteratively with different keys. The encryption should be length-preserving and there is no place for a nonce. For these cases, one can use a tweakable *wide block cipher*. This encrypts arbitrarily large strings in such a way that each bit of the ciphertext depends on each bit of the plaintext and vice versa. If the plaintext changes, the ciphertext will look completely random, even if the change is just a single bitflip.

The idea of wide block ciphers is gaining traction: a notable contribution to the field is Adiantum [CB18], a mode that is specifically developed for disk encryption but still

fares very well as a general wide block cipher mode. Adiantum follows a structure that reminds of Feistel but it is asymmetric. It uses two branches: an arbitrary-length branch for bulk encryption, and a fixed-length branch that is processed using AES and that is used as a seed for encryption of the arbitrary-length branch. A description of Adiantum is given in Appendix A. Adopting arbitrary-length branches appears like a fruitful direction, but decryption requires evaluation of the inverse of AES. Other notable constructions are HEH [NR97], EME [HR04], HCTR [WFW05], AEZ [HKR15], FAST [CGLS17] and Tweakable HCTR [DN18]. We refer to Table 1 for an overview of these modes.

## 1.1 Deck-Based Wide Block Cipher Modes

In this work, we formalize and analyze two similar deck-based tweakable wide block cipher modes: *double-decker* and *docked-double-decker*. Double-decker is an immediate generalization of Farfalle-WBC, a wide block cipher construction proposed by Bertoni et al. [BDH<sup>+</sup>17]. Double-decker follows the well-established Feistel design, but unlike all previous instances, it is based on two arbitrary-length branches and is built upon two arbitrary-length primitives called *doubly-extendable cryptographic keyed (deck) functions*. Deck functions, a notion of Daemen et al. [DHVV18], are cryptographic primitives that have arbitrary-length input and output. In this light, they are *the* natural building block in our wide block cipher mode whose two branches are both arbitrary-length. Double-decker, as such, consists of two Feistel rounds of deck functions surrounded by two Feistel rounds of a keyed hash function.

We also introduce docked-double-decker, a variant of double-decker. It moves the bulk of the input of the deck functions to the keyed hash functions. This illustrates the flexibility that the Feistel structure provides: it does not matter which function absorbs inputs, as long as all input is absorbed by a cryptographic function. Moreover, the input to the deck functions becomes fixed length, as long as the tweak has a fixed length as well. This allows one to conceptually view the deck functions as stream ciphers in this case.

Nonetheless, there is more to the deck-based modes. As deck functions support multiple strings as input, we feed a tweak to the inner rounds. This leads to the actual constructions of Section 4: double-decker depicted in Figure 2 and docked-double-decker depicted in Figure 3.

## 1.2 Version History

This paper is based on the previous publication *Deck-Based Wide Block Cipher Modes and an Exposition of the Blinded Keyed Hashing Model* [GDM19]. In this version, many technical details are skipped, most notably the proofs of the theorems. Other parts are expanded, including the separate Section 7 about possible instantiations of (docked-)double-decker.

## 1.3 Blinded Keyed Hashing Model

Security of cryptographic constructions based on keyed hash functions often relies on the *universality* of the hash function. For example, in the analyses of the schemes listed before, the keyed hash functions are assumed to be  $\varepsilon$ -XOR-universal for some small value of  $\varepsilon$ . However, not all keyed hash functions fit well in this model. An example of such function is Xooffie, whose security claim [DHP<sup>+</sup>18, Claim 2] uses a different security notion. Based on this claim, we introduce a more general security model for keyed hash functions: *blinded keyed hashes (bkh)*.

In a nutshell, bkh does not look at single pairs of inputs at a time, as XOR-universality does, but instead looks at a whole list of queries at the same time. As not every pair of inputs is as bad as the worst case, this formalization allows for a more fine-grained security analysis and allows one to improve the security claim in some cases.

We show that an  $\varepsilon$ -XOR-universal function has a bkh advantage of at most  $\binom{q}{2}\varepsilon$ , but the bound is not necessarily tight. We demonstrate the power of bkh based on Xooffie. In detail, in Section 3.1 we show that the security claim for constructions based on Xooffie increases from 64 bits to 128 bits in the common case, just by changing the security model from XOR-universality to bkh. This gain propagates through the mode, and henceforth our analyses of double-decker and docked-double-decker will be based on the assumption that the keyed hash functions are sufficiently bkh secure.

## 1.4 Security

In Section 5 we prove that a simplified security bound for the deck-based wide block cipher modes is of the form

$$2\mathbf{Adv}^{\text{prf}}(\sigma) + \sum_W 2\mathbf{Adv}^{\text{bkh}}(q_W, \sigma_W), \quad (1)$$

where  $\sigma$  is the total data complexity,  $\sigma_W$  is the data complexity with tweak  $W$ ,  $q_W$  the number of queries with tweak  $W$ ,  $\mathbf{Adv}^{\text{prf}}$  is the prf-advantage of the deck function and  $\mathbf{Adv}^{\text{bkh}}$  is the bkh-advantage of the keyed hash function. Our proof is based on ideas of Iwata and Kurosawa [IK02]. However, a difference is that we base our analysis on the bkh-security of the keyed hash functions rather than their XOR-universality.

## 1.5 Reduced Tweak-Dependence

Noting that the deck-based modes have a  $n$ -bit keyed hash function, a naive security bound would have been of the form

$$2\mathbf{Adv}^{\text{prf}}(\sigma) + 2\mathbf{Adv}^{\text{bkh}}(q, \sigma). \quad (2)$$

In particular, the loss of the keyed hash function is  $\mathbf{Adv}^{\text{bkh}}(q, \sigma)$  directly. This is indeed the case for most existing tweakable wide block ciphers, including Adiantum. However, the deck-based modes are *tweakable* wide block ciphers, and the tweak turns out to allow for notable improvement of the bound. Different tweaks separate the domain, hence the underlying deck function should ideally produce independent outputs resulting in independent permutations. As given in Section 1.4, the security bound is of the form in (1).

The bound of (1) significantly improves over the naive bound of (2) if the maximum number of tweak repetitions is limited. For example, if the cipher is called for  $q/\ell$  tweaks  $W$ , each tweak is used  $\ell$  times and the hash is a traditional  $\varepsilon$ -XOR-universal function with  $\mathbf{Adv}^{\text{bkh}}(q, \sigma) \leq \binom{q}{2}\varepsilon$ , the loss on the keyed hash function in (1) is of the form

$$(q/\ell) \binom{\ell}{2} \varepsilon = (\ell - 1)q\varepsilon \ll \binom{q}{2} \varepsilon, \quad (3)$$

provided that  $\ell \ll q$ . Examples of such functions that would fulfill this include GHASH [NIS07] and Poly1305 [Ber05]. Moreover, if every tweak is used at most once, so  $\ell = 1$ , we see that the mode has no security loss to the keyed hash functions. In this way our modes compare favorably with most other tweakable wide block ciphers (see also Table 1). Of course, queries for different tweaks still influence the first term of (1).

Some applications can take advantage of (3) and use different tweaks in the deck-based modes. We demonstrate this in detail in Section 6 via two use cases. One use case is in the context of disk encryption, in Section 6.1. The use case sets physical SSD sector numbers as tweaks, and relies on the fact that the number of write operations to particular SSD sectors is physically limited [BD10]. In the use case detailed in Section 6.1, an adversary

Table 1: Comparison of double-decker and docked-double-decker with state of the art.  $N$  is the length of the message,  $n$  is a security parameter (i.e., 128 or 256). The cost of keyed hash functions, stream ciphers (SC) and deck functions are displayed as the number of processed bits plus the number of generated bits. The cost of (tweakable) block ciphers ((T)BC) is displayed as only the number of processed bits (or equivalent in the case of AEZ). Refer to Section 1.6 for more information about the properties “Inverse free” and “Reduced tweak-independence”.

Mode	Keyed hash	SC	Deck	(T)BC	Inverse free	Reduced tweak-dependence	Reference
HEH	$4N$	—	—	$N$	no	no	[NR97]
EME	—	—	—	$2N + 2$	no	no	[HR04]
HCTR	$2N$	—	—	$N$	no	no	[WFW05]
AEZ	—	—	—	$N + 4$	yes	no	[HKR15]
FAST	$2N + 4n$	—	—	$N$	yes	no	[CGLS17]
Tweakable HCTR	$2N$	—	—	$N$	no	yes	[DN18]
Adiantum	$2N$	$N$	—	$n$	no	no	[CB18]
Double-decker	$N + 2n$	—	$2N$	—	yes	yes	Figure 2
Docked-double-decker	$2N$	—	$N + 2n$	—	yes	yes	Figure 3

has an advantage of at most  $2^{46}\varepsilon$  on the hash functions with the deck-based modes whereas it would be of the order  $2^{74}\varepsilon$  for the typical security bound that is met by, for example, Adiantum. Here we assume that the differentially uniform function is a traditional  $\varepsilon$ -XOR-universal function. The second use cases is on incremental tweaks, in Section 6.2. Deck functions have the pleasant property that inputs consist of a sequence of an arbitrary number of strings, and in addition, that the inputs are incremental: appending a string to the sequence costs as much as just processing the new string. One can henceforth use our deck-based modes in a stateful manner, where the tweak is dependent on all or most of prior messages exchanged. This way, each new evaluation of the mode is performed for a new tweak, collisions among hash function evaluations for the same tweak cannot occur (as one needs at least two evaluations), and the loss on the keyed hash function, the second term in (1), vanishes.

## 1.6 Comparison with Prior Solutions

Various tweakable block ciphers have appeared over the last years. The most notable examples include HCTR [WFW05], HEH [NR97], FAST [CGLS17], Tweakable HCTR [DN18] and most recently Adiantum [CB18]. A comparison among these ciphers, double-decker and docked-double-decker can be found in Table 1. Most of these constructions resemble a Feistel network. However, (Tweakable) HCTR and Adiantum use a block cipher on a branch. The size of this branch is bounded by the size of a typical block cipher: 128 bits. As the birthday bound applies in some use cases, this limits their security to 64 bits. Furthermore, they require the use of the inverse block cipher, incurring additional implementation cost for most block ciphers. Double-decker and docked-double-decker do not have this limitation, without requiring extra passes over the bulk of the data.

Furthermore, double-decker and docked-double-decker have the nice security property of reduced tweak-dependence (see Section 1.5). This means that collisions in the keyed hash functions do not reduce the security as long as different tweaks were used. A feature that is not fulfilled by many earlier schemes; only by Tweakable HCTR.

For efficiency comparisons, we have to instantiate double-decker and docked-double-decker with concrete functions. See Section 7 for the details. In short, double-decker can be instantiated using the concrete deck function Xoofff and keyed hash function Xooffie [DHVV18, DHP<sup>+</sup>18]. On a low-end CPU these functions process (long) input or

output about 4 times faster than AES. Docked-double-decker can be instantiated with more varied choices as stream ciphers can be used. Concretely, using the same primitive choices as Adiantum one obtains a similar construction with three advantages: (1) it uses no block cipher anymore, (2) its design is more efficient with the block cipher replaced by a stream cipher, strengthened by the fact that the tweak is moved to earlier unused nonce space and (3) it offers more security as the location of the tweak input allows for reduced tweak-dependence.

## 1.7 Related Work

Luby and Rackoff considered the Feistel construction with fixed-length independent pseudorandom function in each round [LR88]. They proved that three rounds are sufficient to obtain a pseudorandom permutation that can be used in forward direction, and four rounds are sufficient to obtain a strong pseudorandom permutation that can be used in both forward and inverse direction. A large amount of research has been aimed at reducing the requirements for the underlying primitives. One way to do so is by reducing the number of independent primitives [Pie90, Pat92]. Another avenue is in replacing cryptographically strong pseudorandom functions by (weaker) universal hash functions. The idea was first suggested by Lucks [Luc96] and was further investigated in [PRS02, IK02]. Particularly relevant to our work is the analysis of Iwata and Kurosawa [IK02] that considered a four-round Feistel construction where the two internal rounds are based on a single pseudorandom function and the two outer rounds on two independent universal hash functions with certain conditions.

Above-mentioned results so far achieve  $n/2$ -bit security, where  $n$  is the size of the branches. Patarin proved security beyond  $n/2$  of the Feistel construction with 5 or more rounds [Pat98, Pat03, Pat04]. We refer to Nachev et al. [NPV17] for a detailed discussion of the security of multiple-round Feistel networks.

One can consider length doublers as a specific type of wide block ciphers. Length doublers use a block cipher with block size  $n$ , and transform it to an encryption primitive that allows encryption of strings of length between  $n$  and  $2n - 1$ . Due to their flexibility, they suit well as building blocks for arbitrary-length (authenticated) encryption. Ristenpart and Rogaway [RR07] introduced the concept in 2007 and presented XLS, a construction later broken by Nandi [Nan14]. Other length doublers are DE by Nandi [Nan09] and HEM by Zhang [Zha12], both based on block ciphers and both birthday-bound secure in the block size of the primitive, and LDT by Chen et al. [CLMP17, CMN18], beyond  $n/2$  secure but based on a tweakable block cipher.

## 2 Preliminaries

### 2.1 Security Model

Our schemes will be parameterized by a security parameter  $n$ . This security parameter will restrict messages to be at least  $2n$  bits long in our mode. For technical reasons we also limit the maximum message size to some natural number  $L$ . This allows us to more easily define a security model, as it is simpler to randomly draw from a finite set. We define message space

$$\mathcal{M} = \bigcup_{i=2n}^L \{0, 1\}^i,$$

key space  $\mathcal{K}$ , and tweak space  $\mathcal{W}$ , and consider a tweakable wide block cipher

$$\mathcal{E} : \mathcal{K} \times \mathcal{W} \times \mathcal{M} \rightarrow \mathcal{M}.$$

For fixed key  $K$ , we write  $\mathcal{E}_K = \mathcal{E}(K, \cdot, \cdot)$ . We require it to preserve length (i.e.,  $|\mathcal{E}_K(W, P)| = |P|$  for any  $(K, W, P) \in \mathcal{K} \times \mathcal{W} \times \mathcal{M}$ ). We also require it to be invertible for fixed  $(K, W) \in \mathcal{K} \times \mathcal{W}$  and denote its inverse with abuse of notation by  $\mathcal{E}_K^{-1}$  (i.e.,  $\mathcal{E}_K^{-1}(W, \mathcal{E}_K(W, P)) = P$  for any  $(K, W, P) \in \mathcal{K} \times \mathcal{W} \times \mathcal{M}$ ).

For a tweakable wide block cipher  $\mathcal{E}$  with security parameter  $n$  and maximum message size  $L$ , the distinguishing advantage of an adversary  $\mathcal{D}$  is

$$\mathbf{Adv}_{\mathcal{E}}^{\pm\text{tprp}}(\mathcal{D}) = \left| \mathbb{P}\left[K \xleftarrow{\$} \mathcal{K} : \mathcal{D}^{\mathcal{E}_K, \mathcal{E}_K^{-1}} = 1\right] - \mathbb{P}\left[\pi \xleftarrow{\$} \text{TPerm}(\mathcal{M}) : \mathcal{D}^{\pi, \pi^{-1}} = 1\right] \right|,$$

where  $\text{TPerm}(\mathcal{M})$  is the set of all length-preserving tweakable permutations over the message space  $\mathcal{M}$ , i.e., the set of all  $\pi : \mathcal{W} \times \mathcal{M} \rightarrow \mathcal{M}$  such that  $|\pi(W, P)| = |P|$  for all  $(W, P) \in \mathcal{W} \times \mathcal{M}$  and  $\pi(W, \cdot)$  invertible for any fixed  $W \in \mathcal{W}$ . Again, we denote its inverse with abuse of notation by  $\pi^{-1}$ .

## 2.2 Deck Functions

We adopt a simplification of the definition of a deck function of Daemen et al. [DHVV18]. A deck (doubly-extendable cryptographic keyed) function  $F$  takes as input a secret key  $K \in \mathcal{K}_F$ , two arbitrarily long strings  $W, X \in \{0, 1\}^*$ , produces a potentially infinite string of bits and takes from it the range starting from a specified offset  $q \in \mathbb{N}$  and for a specified length  $n \in \mathbb{N}$ . We denote this as

$$0^n \oplus F_K(W, X) \ll q.$$

As a deck function has an arbitrary long input and a potentially infinite output, a powerful security definition is that it should behave like a pseudo-random function (prf). This leads to the following security definition for a deck function  $F$ :

$$\mathbf{Adv}_F^{\text{prf}}(L, \mathcal{D}) = \left| \mathbb{P}\left[K \xleftarrow{\$} \mathcal{K}_F : \mathcal{D}^{F_K} = 1\right] - \mathbb{P}\left[G \xleftarrow{\$} \text{PRF}[L] : \mathcal{D}^G = 1\right] \right|,$$

where  $\text{PRF}[L]$  is the set of all pseudo-random functions with two arguments with maximum size  $L$ , i.e., the set of all  $G : \mathcal{X} \times \mathcal{X} \rightarrow \{0, 1\}^L$ , where  $\mathcal{X} = \cup_{i=0}^L \{0, 1\}^i$ . We define

$$\mathbf{Adv}_F^{\text{prf}}(\sigma) = \sup_{\mathcal{D} \in \mathcal{D}(\sigma)} \mathbf{Adv}_F^{\text{prf}}(L, \mathcal{D}),$$

where  $\mathcal{D}(\sigma)$  is the set of all distinguishers such that  $\sum_i \sigma^{(i)} \leq \sigma$ , where  $\sigma^{(i)} = |W^{(i)}| + |X^{(i)}| + n^{(i)}$  is the data complexity of query  $i$  and where  $L = \max_i \sigma^{(i)}$  is the maximum size of the inputs and outputs.

## 2.3 Differentially Uniform Hash Functions

Consider a keyed hash  $H = \{H_K : \{0, 1\}^* \rightarrow \{0, 1\}^n \mid K \in \mathcal{K}_H\}$ . It is called  $\varepsilon$ -XOR-universal if for any two distinct elements  $X, X' \in \{0, 1\}^*$  and any element  $Y \in \{0, 1\}^n$

$$\mathbb{P}\left[K \xleftarrow{\$} \mathcal{K}_H : H_K(X) \oplus H_K(X') = Y\right] \leq \varepsilon.$$

The value  $\varepsilon$  is typically of the form  $2^{a-n}$  for a small value  $a$ .

## 3 Blinded Keyed Hashes

Consider a keyed hash  $H = \{H_K : \{0, 1\}^* \rightarrow \{0, 1\}^n \mid K \in \mathcal{K}_H\}$ . We do not look at its output directly, instead we first blind it through a random oracle: a function that returns an independent random value for every new input. The keyed hash is called a *blinded keyed hash (bkh)* if the distinguishing advantage between the following two worlds, with inputs  $(X, \Delta)$ , is small:

- Real world  $\mathcal{O}$ :  $\mathcal{RO}_1(H_K(X) \oplus \Delta)$  with  $K \xleftarrow{\$} \mathcal{K}_H$  and a secret random oracle  $\mathcal{RO}_1$ ;
- Ideal world  $\mathcal{P}$ :  $\mathcal{RO}_2(X, \Delta)$  with a secret random oracle  $\mathcal{RO}_2$ .




Figure 1: The distinguishability setup for bkh. Left is the real world  $\mathcal{O}$  and right is the ideal world  $\mathcal{P}$ .

We denote its advantage by

$$\mathbf{Adv}_H^{\text{bkh}}(\mathcal{D}) = |\mathbb{P}[\mathcal{D}^{\mathcal{O}} = 1] - \mathbb{P}[\mathcal{D}^{\mathcal{P}} = 1]|.$$

For a fixed list of queries  $Q$ , we define

$$\mathbf{Adv}_H^{\text{bkh}}(Q) = \sup_{\mathcal{D} \in \mathcal{D}(Q)} \mathbf{Adv}_H^{\text{bkh}}(\mathcal{D}),$$

where  $\mathcal{D}(Q)$  is the set of all distinguishers that make the fixed list of queries  $Q$ . And for a total number of  $q$  queries with data complexity  $\sigma = \sum_i |X^{(i)}| + |\Delta^{(i)}|$ , we define

$$\mathbf{Adv}_H^{\text{bkh}}(q, \sigma) = \sup_{\mathcal{D} \in \mathcal{D}(q, \sigma)} \mathbf{Adv}_H^{\text{bkh}}(\mathcal{D}),$$

where  $\mathcal{D}(q, \sigma)$  is the set of all distinguishers that make at most  $q$  queries with data complexity  $\sigma = \sum_i |X^{(i)}| + |\Delta^{(i)}|$ .

### 3.1 Relation to Differentially Uniform Functions

The more common definition of differentially uniform functions given in Section 2.3 is roughly equivalent to the definition of blinded keyed hashes. Proposition 1 shows the relation between  $\varepsilon$ -XOR-universal and bkh functions. We can reduce any  $\varepsilon$  to a bkh advantage bound and vice-versa, but the  $\varepsilon$ -XOR-universal definition is more strict. It requires an upper bound  $\varepsilon$  on the probability of collisions, but not all inputs have to be near this  $\varepsilon$  as the probabilities do not have to be uniform. On the other hand, the bkh definition allows for more flexibility as it looks at a list of queries and makes a claim about an attack as a whole. Indeed, some functions have much better guarantees with the bkh definition than the  $\varepsilon$ -XOR-universal one. For example Xooffie has the following security claim [DHP<sup>+</sup>18, Claim 2]:

$$\mathbf{Adv}_{\text{Xooffie}}^{\text{bkh}}(q, \sigma) \leq \frac{M}{2^{128}} + \frac{M^2}{2^{n-4}},$$

where  $M = \lceil \sigma/384 \rceil$  is the data complexity expressed in the number of input blocks and where  $n$  can be chosen variably. If  $n - 4$  is larger than 256, the quadratic term is negligible and Xooffie claims to have around 128 bits of security. We would not get this level of security in the claim when we look at the traditional  $\varepsilon$ -XOR-universal definition. By



Proposition 1, Xooffie is  $\varepsilon$ -XOR-universal with

$$\begin{aligned}\varepsilon &= \mathbf{Adv}_{\text{Xooffie}}^{\text{bkh}}(2, 2 \cdot 384) \\ &\leq \frac{2}{2^{128}} + \frac{2^2}{2^{n-4}} \\ &\approx 2^{-127}.\end{aligned}$$

Here, we assume that Xooffie is only called with one block inputs. If it is called with more input, its  $\varepsilon$ -XOR-universal security becomes even worse. However, with this definition we approximate the advantage of Xooffie as  $\binom{q}{2}/2^{127} \leq \binom{M}{2}/2^{127}$ , which would suggest that Xooffie only has around 64 bits of security. By using the bkh definition, we can make use of these better security properties.

To our knowledge, the only currently known cryptographic primitive with a bkh-model security claim is Xooffie [DHP<sup>+</sup>18, Claim 2]. As a bkh claim is more general than a differential-uniformity one, proofs using the bkh-model are also valid for the latter. However, conversely, a bkh-model security claim can give a better security bound for high data complexity. In particular, in Farfalle-like keyed hash functions, similar claims can be made when using permutations such as the Ascon permutation [DEMS16], Gimli [BKL<sup>+</sup>17] or Keccak- $p[r = 6]$  as in Kravatte [BDH<sup>+</sup>17].

**Proposition 1.** *The following two properties hold.*

1. *If  $H$  is  $\varepsilon$ -XOR-universal, then  $H$  is bkh with advantage  $\mathbf{Adv}_H^{\text{bkh}}(q, \sigma) \leq \varepsilon \binom{q}{2}$ .*
2. *If  $H$  is bkh, then  $H$  is  $\varepsilon$ -XOR-universal with  $\varepsilon = \mathbf{Adv}_H^{\text{bkh}}(2, 2l)$ , where  $l$  is the maximum allowed query length.*

The proof of Proposition 1 can be found in the original publication [GDM19].

## 4 Deck-Based Wide Block Cipher Modes

We introduce two modes: double-decker, directly based on Farfalle-WBC [BDH<sup>+</sup>17], and docked-double-decker, a slight modification of double-decker that moves the bulk of the input from the deck functions to the hash functions.


Double-decker and docked-double-decker are tweakable wide block ciphers that take as input three keys  $(K, K_1, K_2) \in \mathcal{K} = \mathcal{K}_H \times \mathcal{K}_F \times \mathcal{K}_F$ , a tweak  $W \in \mathcal{W}$ , and a message  $P \in \mathcal{M}$ , and transform it to a ciphertext  $C \in \mathcal{M}$ . Instead of using two keys  $K_1, K_2 \in \mathcal{K}_F$ , it is also possible to use a single key and apply domain separation between the functions, as that gives two independent functions as well. Both double-decker and docked-double-decker are a generalized four-round Feistel construction based on two independent deck functions  $F_{K_1}$  and  $F_{K_2}$  and two evaluations of a bkh function  $H_K$ .

Double-decker is illustrated in Figure 2. Here, the message  $P$  is first split into the inputs to the two branches  $U$  and  $V$  using a split function *split*. This function *split* takes as input the length of the message  $P$  and outputs the length of the left branch,  $|U|$ . The states  $U$  and  $V$  are further split into  $U_L, U_R, V_L$  and  $V_R$  with the outside branches length  $n$ , so  $|U_L| = |V_R| = n$ . This means that we have a condition that  $n \leq \text{split}(|P|) \leq |P| - n$  for all  $P$ . In other words, *split* can be an arbitrary function, as long as it is defined for input strings of at least  $2n$  bits, and its corresponding branches are of length at least  $n$ .

Docked-double-decker is illustrated in Figure 3. It is similar to double-decker, but with two differences. First, the branch  $V_L$  is removed, i.e.  $\text{split}(|P|) = |P| - n$ . Second, the bulk of the input to  $F_{K_1}$ , on branch  $U_R$ , is moved from the deck function  $F_{K_1}$  to the first bkh function  $H_K$ . This illustrates the flexibility that the Feistel structure provides: it does not matter which function absorbs inputs, as long as all input is absorbed by a cryptographic



function. Moreover, the input to the deck functions  $F_{K_1}$  and  $K_{K_2}$  becomes fixed length, as long as the tweak has a fixed length as well. This allows one to conceptually view the deck functions as stream ciphers in this case.



```

function ENCRYPT( $W, P$ )
   $U\|V \leftarrow P$ , with  $|U| = \text{split}(|P|)$ 
   $L \leftarrow U \oplus (H_K(V) \parallel 0^{|U|-n})$ 
   $R \leftarrow V \oplus F_{K_1}(W, L)$ 
   $X \leftarrow L \oplus F_{K_2}(W, Y)$ 
   $Y \leftarrow R \oplus (0^{|R|-n} \parallel H_K(X))$ 
   $C \leftarrow X\|Y$ 
  return  $C$ 


```

```

function DECRYPT( $W, C$ )
   $X\|Y \leftarrow C$ , with  $|X| = \text{split}(|C|)$ 
   $R \leftarrow Y \oplus (0^{|Y|-n} \parallel H_K(X))$ 
   $L \leftarrow X \oplus F_{K_2}(W, R)$ 
   $V \leftarrow R \oplus F_{K_1}(W, L)$ 
   $U \leftarrow L \oplus (H_K(V) \parallel 0^{|L|-n})$ 
   $P \leftarrow U\|V$ 
  return  $P$ 

```

Figure 2: Double-decker tweakable wide block cipher. The parsing of  $P$  into states  $U_L, U_R, V_L, V_R$ , where  $|U_L| = |V_R| = n$  and  $|U| = \text{split}(|P|)$  is not depicted.



```

function ENCRYPT( $W, P$ )
   $T\|U\|V \leftarrow P$ , with  $|T| = |V| = n$ 
   $L \leftarrow T \oplus H_K(U\|V)$ 
   $R \leftarrow V \oplus F_{K_1}(W, L)$ 
   $X \leftarrow L \oplus F_{K_2}(W, R)$ 
   $Y \leftarrow U \oplus F_{K_2}(W, R) \lll n$ 
   $Z \leftarrow R \oplus H_K(X\|Y)$ 
   $C \leftarrow X\|Y\|Z$ 
  return  $C$ 

```

```

function DECRYPT( $W, C$ )
   $X\|Y\|Z \leftarrow C$ , with  $|X| = |Z| = n$ 
   $R \leftarrow Z \oplus (H_K(X\|Y))$ 
   $L \leftarrow X \oplus F_{K_2}(W, R)$ 
   $U \leftarrow Y \oplus F_{K_2}(W, R) \lll n$ 
   $V \leftarrow R \oplus F_{K_1}(W, L)$ 
   $T \leftarrow L \oplus (H_K(U\|V))$ 
   $P \leftarrow T\|U\|V$ 
  return  $P$ 

```

Figure 3: Docked-double-decker tweakable wide block cipher. The parsing of  $P$  into states  $T, U, V$ , where  $|T| = |V| = n$  is not depicted.

## 5 Analysis

We prove security of both the double-decker and the docked-double-decker construction of Section 4.

**Theorem 1.** *Let  $\mathcal{E}$  be either the double-decker construction or the docked-double-decker construction of Section 4. For any distinguisher  $\mathcal{D}$  making at most  $q$  queries with a length of at most  $L$ , we have*

$$\begin{aligned} \mathbf{Adv}_{\mathcal{E}}^{\pm\text{tprp}}(\mathcal{D}) &\leq \mathbf{Adv}_F^{\text{prf}}(\sigma_{F_1}) + \mathbf{Adv}_F^{\text{prf}}(\sigma_{F_2}) \\ &\quad + \sum_{W \in \mathcal{W}} \left( \mathbf{Adv}_H^{\text{bkh}}(q_W, \sigma_{H_1, W}) + \mathbf{Adv}_H^{\text{bkh}}(q_W, \sigma_{H_2, W}) + \binom{q_W}{2} 2^{-2n} \right), \end{aligned}$$

where  $\sigma_{F_1}, \sigma_{F_2}$  are the total data complexities on each  $F$  and where  $\sigma_{H_1, W}, \sigma_{H_2, W}$  are the data complexities on each  $H$  and  $q_W$  is the number of queries with tweak  $W$  made by distinguisher  $\mathcal{D}$ . For double-decker we have

$$\begin{aligned} \sigma_{F_1} = \sigma_{F_2} &= \sum_{i=1}^q |W^{(i)}| + |P^{(i)}|, \\ \sigma_{H_1, W} &= \sum_{\substack{i=1 \\ W^{(i)}=W}}^q |P^{(i)}| - \text{split}(|P^{(i)}|) + n, \\ \sigma_{H_2, W} &= \sum_{\substack{i=1 \\ W^{(i)}=W}}^q \text{split}(|P^{(i)}|) + n. \end{aligned}$$

For docked-double-decker we have

$$\begin{aligned} \sigma_{F_1} &= \sum_{i=1}^q |W^{(i)}| + 2n, \\ \sigma_{F_2} &= \sum_{i=1}^q |W^{(i)}| + |P^{(i)}|, \\ \sigma_{H_1, W} = \sigma_{H_2, W} &= \sum_{\substack{i=1 \\ W^{(i)}=W}}^q |P^{(i)}|. \end{aligned}$$

The proof of Theorem 1 can be found in the original publication [GDM19].

## 6 Application

### 6.1 Disk Encryption

In our deck-based modes, a naive security loss to the hash functions would be of the form  $2\mathbf{Adv}_H^{\text{bkh}}(q, \sigma)$ , where  $q$  is the total number of queries and  $\sigma$  the total data complexity. However, the more fine-grained security loss given in Theorem 1 is of the form  $\sum_{W \in \mathcal{W}} 2\mathbf{Adv}_H^{\text{bkh}}(q_W, \sigma_W)$ , where  $q_W$  is the number of queries and  $\sigma_W$  the data complexity with tweak  $W$ . This is a significant improvement over the naive security loss for some functions if the tweak varies a lot. It does not give a real improvement for hash functions with a more linear security loss in the bkh model. However, some hash functions have a quadratic security loss, even in the bkh model. Examples of such functions include GHASH [NIS07] and Poly1305 [Ber05]. In these cases, the naive security loss to the hash

functions would be of the form  $2\binom{q}{2}\varepsilon$  and the more fine-grained one given in Theorem 1 would be of the form  $\sum_{W \in \mathcal{W}} 2\binom{q_W}{2}\varepsilon$ .

This turns out to give a significant gain in the context of disk encryption, if the deck-based modes are called with the physical sector number as tweak. In this case, every sector basically gets its own dedicated wide block cipher. This is especially useful in the context of SSDs. As SSDs get damaged every time data is written to a sector, the firmware of the SSD tries to distribute the data uniformly over its sectors [GT05]. If a sector is written to too many times, the sector cannot be used anymore [BD10]. In the context of the bound of Theorem 1, this means that the distinguisher is limited in its attack: every tweak can only be used at most a constant number of times.

We outline the gain with a concrete example. The Kingston UV500 960 GB [Kin18] has a Total Bytes Written specification of 480 TB. This means that every sector can be written at most  $480\text{TB}/960\text{GB} = 500$  times. For a sector size of 4 KiB, which implies  $N = 960\text{GB}/4\text{KiB} \approx 2^{28}$  sectors, this concretely means a security loss on the hash functions of

$$2N \binom{500}{2} \varepsilon \approx 2^{46} \varepsilon.$$

This is an improvement over the typical birthday bound of

$$2 \binom{500N}{2} \varepsilon \approx 2^{74} \varepsilon$$

that would we achieved by, for example, Adiantum [CB18]. Concretely, the security level goes up  $\log_2 N$  bits, and the gain would become particularly meaningful if  $\varepsilon$  is not very small.

## 6.2 Incremental Tweak

Following Daemen et al. [DHVV18], deck functions have two features:

- (i) their inputs consist of a sequence of an arbitrary number of strings, each of arbitrary length;
- (ii) their inputs are *incremental*: appending a string to the input sequence costs only the processing of the new string.

These features, along with the reduced tweak-dependence of the bounds of our constructions, leads to pleasant use cases for double-decker and docked-double-decker.

In more detail, in our constructions we already make use of feature (i) by presenting the tweak and intermediate result as a sequence of two strings. We do not yet use feature (ii). However, suppose we make the tweak dependent on prior messages exchanged, or in general on the history of the protocol. It suffices to clone the state of the deck function after absorbing the new tweak string and in the next construction call start from this state. The tweak used in the computation of a construction call will consist of the sequence of the tweak strings that were absorbed in all previous construction calls. This tweak is *different* for each evaluation of double-decker/docked-double-decker, which, in the context of the security bound, implies  $q_W = 1$  for each tweak  $W$ . Note that this use case comes at modest cost only: by incrementality (feature (ii)), appending data to the earlier sequence costs only the processing of the new string.

We remark that this use case is not far-fetched: similar ideas may be found in several modern protocols. One example is the TLS handshake [TD08], where a hash is computed over all steps and where only this hash is signed later on. Another example is the STROBE protocol framework of Hamburg [Ham17]. STROBE makes use of stateful objects in such a way that all strings absorbed by the object impact its state. Hence, any output generated by the stateful object depends on the concatenation of all that came before.

## 7 Instantiations

To evaluate the efficiency of the deck-based modes, we need to look into instantiations with concrete deck functions and keyed hash functions. We consider instantiations for both double-decker and docked-double-decker.

### 7.1 Double-decker

Recently, concrete deck functions and keyed hash functions have been proposed in [BDH<sup>+</sup>17], Kravatte and Short-Kravatte, and in [DHVV18, DHP<sup>+</sup>18], Xooff and Xooffie. The former are built on the 1600-bit permutation Keccak- $p$  with 6 rounds and the latter on the 384-bit permutation Xoodoo. For the latter, [DHVV18, Table 5] gives performance numbers. On ARM Cortex M0 and M3, representative for low-end CPU, Xooff and Xooffie process (long) input or output about 4 times faster than AES. So a Xooff call with  $N$  bits of input and  $M$  bits of output is about four times as fast as applying AES-128 CBC-MAC to an  $N$ -bit input and then AES-128 in counter mode generating an  $M$ -bit keystream.

On high-end CPUs like Intel Skylake the presence of dedicated AES instructions makes the difference between Xooff and AES smaller, but still on the recent Intel SkylakeX, Xooff beats AES in speed.

Of course Xooff has not gone through the amount of scrutiny that Rijndael/AES has, but these performance numbers indicate that there is great potential should Xooff and Xooffie turn out to stand up to their security claims, that are actually much more ambitious than those of AES.

### 7.2 Docked-double-decker

Docked-double-decker is a bit more general and has less assumptions on the primitive used. It still uses a keyed hash, but it does not require a deck function, just a stream cipher. These can still be instantiated by Xooffie and Xooff, although the generality allows for other choices as well. For example, the primitives used in Adiantum [CB18], a combination of NH [Kro00] and Poly1305 [Ber05] for the keyed hash function and XChaCha12 [B<sup>+</sup>08, Ber11] for the stream cipher, are still compatible with docked-double-decker. Like Adiantum, the small lanes remain 128 bits, but unlike it the tweak is moved to the stream cipher. As XChaCha12 takes a 192-bit nonce, there is still sufficient room for a 64-bit tweak. Additionally, this move of the tweak allows for the use of reduced tweak-dependence. In short, docked-double-decker with these primitives has the following advantages over Adiantum:

1. Less primitives: docked-double-decker reduces the number of primitives used from 3 to 2, eliminating the use of a block cipher completely.
2. Arguably more efficient design: as the block cipher is replaced with a stream cipher while maintaining the same number of passes over the data, docked-double-decker has a more efficient design than Adiantum. Furthermore, docked-double-decker moves the location of the tweak to previously unused space in the nonce of XChaCha12, slightly reducing the input to the keyed hash functions, which also slightly increases the efficiency.
3. More security in certain settings: another improvement of moving the tweak input to the nonce of the stream cipher is that this allows for reduced tweak-dependence. This, depending on the application, reduces the contribution of the keyed hash function in the security bound, improving the security of the construction.

The only limitations are that the minimum size is  $2n$  instead of  $n$ , with  $n$  the size of the small lane(s), and that the size of the tweak is limited to 64 bits. As a stream cipher needs  $n$  bits as input and also needs to output  $n$  bits to have a good security bound, it looks improbable that the minimum size of  $2n$  can be reduced without having an invertible primitive like a block cipher. However, in many applications, including disk encryption, this minimum required size and only having a 64-bit tweak are no problem.

Although the usage of the tweak in docked-double-decker requires a longer nonce for the stream cipher, this limitation can be averted by moving the tweak from the stream ciphers to the keyed hash functions. The security proof remains very similar, but there is one important difference: tweak-dependence. Where both double-decker and docked-double-decker enjoy reduced tweak-dependence, this modification removes it.

ACKNOWLEDGMENTS. The authors would like to thank Seth Hoffert, Gilles Van Assche and the anonymous reviewers of ToSC for their valuable feedback. Aldo Gunging is supported by the Netherlands Organisation for Scientific Research (NWO) under TOP grant TOP1.18.002 SCALAR. Joan Daemen is supported by the European Research Council under the ERC advanced grant agreement under grant ERC-2017-ADG Nr. 788980 ESCADA. Bart Mennink is supported by the Netherlands Organisation for Scientific Research (NWO) under grant VI.Vidi.203.099.

## References

- [B<sup>+</sup>08] Daniel J Bernstein et al. Chacha, a variant of salsa20. In *Workshop record of SASC*, volume 8, pages 3–5. Citeseer, 2008.
- [BD10] Simona Boboila and Peter Desnoyers. Write Endurance in Flash Drives: Measurements and Analysis. In Randal C. Burns and Kimberly Keeton, editors, *8th USENIX Conference on File and Storage Technologies, San Jose, CA, USA, February 23-26, 2010*, pages 115–128. USENIX, 2010.
- [BDH<sup>+</sup>17] Guido Bertoni, Joan Daemen, Seth Hoffert, Michaël Peeters, Gilles Van Assche, and Ronny Van Keer. Farfalle: parallel permutation-based cryptography. *IACR Trans. Symmetric Cryptol.*, 2017(4):1–38, 2017.
- [Ber05] Daniel J. Bernstein. The Poly1305-AES Message-Authentication Code. In Henri Gilbert and Helena Handschuh, editors, *Fast Software Encryption: 12th International Workshop, FSE 2005, Paris, France, February 21-23, 2005, Revised Selected Papers*, volume 3557 of *Lecture Notes in Computer Science*, pages 32–49. Springer, 2005.
- [Ber11] Daniel J Bernstein. Extending the salsa20 nonce. In *Workshop record of Symmetric Key Encryption Workshop*, volume 2011, 2011.
- [BKL<sup>+</sup>17] Daniel J. Bernstein, Stefan Kölbl, Stefan Lucks, Pedro Maat Costa Massolino, Florian Mendel, Kashif Nawaz, Tobias Schneider, Peter Schwabe, François-Xavier Standaert, Yosuke Todo, and Benoît Viguier. Gimli : A Cross-Platform Permutation. In Wieland Fischer and Naofumi Homma, editors, *Cryptographic Hardware and Embedded Systems - CHES 2017 - 19th International Conference, Taipei, Taiwan, September 25-28, 2017, Proceedings*, volume 10529 of *Lecture Notes in Computer Science*, pages 299–320. Springer, 2017.
- [CB18] Paul Crowley and Eric Biggers. Adiantum: length-preserving encryption for entry-level processors. *IACR Trans. Symmetric Cryptol.*, 2018(4):39–61, 2018.

- [CGLS17] Debrup Chakraborty, Sebati Ghosh, Cuauhtemoc Mancillas Lopez, and Palash Sarkar. Fast: Disk encryption and beyond. Cryptology ePrint Archive, Report 2017/849, 2017.
- [CLMP17] Yu Long Chen, Atul Luykx, Bart Mennink, and Bart Preneel. Efficient Length Doubling From Tweakable Block Ciphers. *IACR Trans. Symmetric Cryptol.*, 2017(3):253–270, 2017.
- [CMN18] Yu Long Chen, Bart Mennink, and Mridul Nandi. Short Variable Length Domain Extenders with Beyond Birthday Bound Security. In Thomas Peyrin and Steven D. Galbraith, editors, *Advances in Cryptology - ASIACRYPT 2018 - 24th International Conference on the Theory and Application of Cryptology and Information Security, Brisbane, QLD, Australia, December 2-6, 2018, Proceedings, Part I*, volume 11272 of *Lecture Notes in Computer Science*, pages 244–274. Springer, 2018.
- [DEMS16] Christoph Dobraunig, Maria Eichlseder, Florian Mendel, and Martin Schl affer. Ascon v1.2. Submission to Round 3 of the CAESAR competition, 2016.
- [DHP<sup>+</sup>18] Joan Daemen, Seth Hoffert, Micha el Peeters, Gilles Van Assche, and Ronny Van Keer. Xoodoo cookbook. Cryptology ePrint Archive, Report 2018/767, 2018.
- [DHVV18] Joan Daemen, Seth Hoffert, Gilles Van Assche, and Ronny Van Keer. The design of Xoodoo and Xooff. *IACR Trans. Symmetric Cryptol.*, 2018(4):1–38, 2018.
- [DN18] Avijit Dutta and Mridul Nandi. Tweakable HCTR: A BBB Secure Tweakable Enciphering Scheme. In Debrup Chakraborty and Tetsu Iwata, editors, *Progress in Cryptology - INDOCRYPT 2018 - 19th International Conference on Cryptology in India, New Delhi, India, December 9-12, 2018, Proceedings*, volume 11356 of *Lecture Notes in Computer Science*, pages 47–69. Springer, 2018.
- [GDM19] Aldo Gunsing, Joan Daemen, and Bart Mennink. Deck-based wide block cipher modes and an exposition of the blinded keyed hashing model. *IACR Trans. Symmetric Cryptol.*, 2019(4):1–22, 2019.
- [GT05] Eran Gal and Sivan Toledo. Algorithms and data structures for flash memories. *ACM Comput. Surv.*, 37(2):138–163, 2005.
- [Ham17] Mike Hamburg. The STROBE protocol framework. Cryptology ePrint Archive, Report 2017/003, 2017.
- [HKR15] Viet Tung Hoang, Ted Krovetz, and Phillip Rogaway. Robust Authenticated-Encryption AEZ and the Problem That It Solves. In Elisabeth Oswald and Marc Fischlin, editors, *Advances in Cryptology - EUROCRYPT 2015 - 34th Annual International Conference on the Theory and Applications of Cryptographic Techniques, Sofia, Bulgaria, April 26-30, 2015, Proceedings, Part I*, volume 9056 of *Lecture Notes in Computer Science*, pages 15–44. Springer, 2015.
- [HR04] Shai Halevi and Phillip Rogaway. A Parallelizable Enciphering Mode. In Tatsuaki Okamoto, editor, *Topics in Cryptology - CT-RSA 2004, The Cryptographers’ Track at the RSA Conference 2004, San Francisco, CA, USA, February 23-27, 2004, Proceedings*, volume 2964 of *Lecture Notes in Computer Science*, pages 292–304. Springer, 2004.

- [IK02] Tetsu Iwata and Kaoru Kurosawa. On the Universal Hash Functions in Luby-Rackoff Cipher. In Pil Joong Lee and Chae Hoon Lim, editors, *Information Security and Cryptology - ICISC 2002, 5th International Conference Seoul, Korea, November 28-29, 2002, Revised Papers*, volume 2587 of *Lecture Notes in Computer Science*, pages 226–236. Springer, 2002.
- [Kin18] Kingston. UV500 Encrypted SSD. [https://www.kingston.com/datasheets/SUV500\\_us.pdf](https://www.kingston.com/datasheets/SUV500_us.pdf), 2018.
- [Kro00] Theodore Dennis Krovetz. *Software-optimized universal hashing and message authentication*. PhD thesis, 2000.
- [LR88] Michael Luby and Charles Rackoff. How to Construct Pseudorandom Permutations from Pseudorandom Functions. *SIAM J. Comput.*, 17(2):373–386, 1988.
- [Luc96] Stefan Lucks. Faster Luby-Rackoff Ciphers. In Dieter Gollmann, editor, *Fast Software Encryption, Third International Workshop, Cambridge, UK, February 21-23, 1996, Proceedings*, volume 1039 of *Lecture Notes in Computer Science*, pages 189–203. Springer, 1996.
- [Nan09] Mridul Nandi. A Generic Method to Extend Message Space of a Strong Pseudorandom Permutation. *Computación y Sistemas*, 12(3), 2009.
- [Nan14] Mridul Nandi. XLS is Not a Strong Pseudorandom Permutation. In Palash Sarkar and Tetsu Iwata, editors, *Advances in Cryptology - ASIACRYPT 2014 - 20th International Conference on the Theory and Application of Cryptology and Information Security, Kaoshiung, Taiwan, R.O.C., December 7-11, 2014. Proceedings, Part I*, volume 8873 of *Lecture Notes in Computer Science*, pages 478–490. Springer, 2014.
- [NIS07] NIST. NIST special publication 800-38D, recommendation for block cipher modes of operation: Galois/counter mode (GCM) and GMAC, November 2007.
- [NPV17] Valérie Nachev, Jacques Patarin, and Emmanuel Volte. *Feistel Ciphers - Security Proofs and Cryptanalysis*. Springer, 2017.
- [NR97] Moni Naor and Omer Reingold. A pseudo-random encryption mode, 1997.
- [Pat92] Jacques Patarin. How to Construct Pseudorandom and Super Pseudorandom Permutations from one Single Pseudorandom Function. In Rainer A. Rueppel, editor, *Advances in Cryptology - EUROCRYPT '92, Workshop on the Theory and Application of Cryptographic Techniques, Balatonfüred, Hungary, May 24-28, 1992, Proceedings*, volume 658 of *Lecture Notes in Computer Science*, pages 256–266. Springer, 1992.
- [Pat98] Jacques Patarin. About Feistel Schemes with Six (or More) Rounds. In Serge Vaudenay, editor, *Fast Software Encryption, 5th International Workshop, FSE '98, Paris, France, March 23-25, 1998, Proceedings*, volume 1372 of *Lecture Notes in Computer Science*, pages 103–121. Springer, 1998.
- [Pat03] Jacques Patarin. Luby-Rackoff: 7 Rounds Are Enough for  $2^{n(1-\epsilon)}$  Security. In Dan Boneh, editor, *Advances in Cryptology - CRYPTO 2003, 23rd Annual International Cryptology Conference, Santa Barbara, California, USA, August 17-21, 2003, Proceedings*, volume 2729 of *Lecture Notes in Computer Science*, pages 513–529. Springer, 2003.



- [Pat04] Jacques Patarin. Security of Random Feistel Schemes with 5 or More Rounds. In Matthew K. Franklin, editor, *Advances in Cryptology - CRYPTO 2004, 24th Annual International Cryptology Conference, Santa Barbara, California, USA, August 15-19, 2004, Proceedings*, volume 3152 of *Lecture Notes in Computer Science*, pages 106–122. Springer, 2004.
- [Pie90] Josef Pieprzyk. How to Construct Pseudorandom Permutations from Single Pseudorandom Functions. In Ivan Damgård, editor, *Advances in Cryptology - EUROCRYPT '90, Workshop on the Theory and Application of Cryptographic Techniques, Aarhus, Denmark, May 21-24, 1990, Proceedings*, volume 473 of *Lecture Notes in Computer Science*, pages 140–150. Springer, 1990.
- [PRS02] Sarvar Patel, Zulfikar Ramzan, and Ganapathy S. Sundaram. Luby-Rackoff Ciphers: Why XOR Is Not So Exclusive. In Kaisa Nyberg and Howard M. Heys, editors, *Selected Areas in Cryptography, 9th Annual International Workshop, SAC 2002, St. John's, Newfoundland, Canada, August 15-16, 2002. Revised Papers*, volume 2595 of *Lecture Notes in Computer Science*, pages 271–290. Springer, 2002.
- [RR07] Thomas Ristenpart and Phillip Rogaway. How to Enrich the Message Space of a Cipher. In Alex Biryukov, editor, *Fast Software Encryption, 14th International Workshop, FSE 2007, Luxembourg, Luxembourg, March 26-28, 2007, Revised Selected Papers*, volume 4593 of *Lecture Notes in Computer Science*, pages 101–118. Springer, 2007.
- [TD08] E. Rescorla T. Dierks. The Transport Layer Security (TLS) Protocol Version 1.2. Network Working Group of the IETF, RFC 5246, August 2008.
- [WFW05] Peng Wang, Dengguo Feng, and Wenling Wu. HCTR: A variable-input-length enciphering mode. In Dengguo Feng, Dongdai Lin, and Moti Yung, editors, *Information Security and Cryptology, First SKLOIS Conference, CISC 2005, Beijing, China, December 15-17, 2005, Proceedings*, volume 3822 of *Lecture Notes in Computer Science*, pages 175–188. Springer, 2005.
- [Zha12] Haibin Zhang. Length-Doubling Ciphers and Tweakable Ciphers. In Feng Bao, Pierangela Samarati, and Jianying Zhou, editors, *Applied Cryptography and Network Security - 10th International Conference, ACNS 2012, Singapore, June 26-29, 2012. Proceedings*, volume 7341 of *Lecture Notes in Computer Science*, pages 100–116. Springer, 2012.

## A Adiantum

Adiantum is a (tweakable) wide block cipher design of Crowley and Biggers [CB18]. We describe its mode, in our notation and terminology, in Figure 4. Here,  $H$  is a  $\varepsilon$ -almost- $\Delta$ -universal hash function,  $F$  a stream cipher, and  $B$  a block cipher.




Figure 4: Adiantum mode (originally called HBSH in [CB18]).