



LEVEL 3 SECURITY POLICY FOR

Luna® PCI Cryptographic Module For Luna® IS

DOCUMENT NUMBER:	CR-2333
AUTHOR:	Terry Fletcher
DEPARTMENT:	Engineering
LOCATION OF ISSUE:	Ottawa
DATE ORIGINATED:	January 30, 2007
REVISION LEVEL:	17
REVISION DATE:	July 22, 2009
SUPERSESION DATA:	CR-2333, Rev. 16
SECURITY LEVEL:	

© Copyright 2007-2009 SafeNet, Inc.

ALL RIGHTS RESERVED

This document may be freely reproduced and distributed whole and intact including this copyright notice.

SafeNet, Inc. reserves the right to make changes in the product or its specifications mentioned in this publication without notice. Accordingly, the reader is cautioned to verify that information in this publication is current before placing orders. The information furnished by SafeNet, Inc. in this document is believed to be accurate and reliable. However, no responsibility is assumed by SafeNet, Inc. for its use, or for any infringements of patents or other rights of third parties resulting from its use.

TABLE OF CONTENTS

Section	Title	Page
1.	INTRODUCTION	1
1.1.	Purpose	1
1.2.	Scope	1
2.	SECURITY POLICY MODEL INTRODUCTION	1
2.1.	Functional Overview	1
2.2.	Assets to be Protected	2
2.3.	Operating Environment	2
3.	SECURITY POLICY MODEL DESCRIPTION	3
3.1.	Operational Policy	3
3.1.1.	Module Capabilities	4
3.1.2.	Partition Capabilities	4
3.2.	FIPS-Approved Mode	9
3.3.	Description of Operator, Subject and Object	9
3.3.1.	Operator	9
3.3.2.	Roles	9
3.3.3.	Account Data	10
3.3.4.	Subject	11
3.3.5.	Operator – Subject Binding	11
3.3.6.	Object	11
3.3.7.	Object Operations	11
3.4.	Identification and Authentication	12
3.4.1.	Authentication Data Generation and Entry	12
3.4.2.	Trusted Path	12
3.4.2.1.	Remote PED Operation	12
3.4.3.	M of N Authentication	13
3.4.4.	Limits on Login Failures	13
3.5.	Access Control	13
3.5.1.	Object Re-use	15
3.5.2.	Privileged Functions	15
3.6.	Cryptographic Material Management	15
3.7.	Cryptographic Operations	16
3.8.	Self-tests	17
3.9.	Firmware Security	17



3.10.	Physical Security	18
3.11.	EMI/EMC	18
3.12.	Fault Tolerance.....	18
3.13.	Mitigation of Other Attacks	18

LIST OF TABLES

Table	Title	Page
Table 3-1	Module Capabilities and Policies	5
Table 3-2	Partition Capabilities and Policies	6
Table 3-3	Object Attributes Used in Access Control Policy Enforcement.....	14
Table 3-4.	Algorithm Validation Certificates	17
Table 3-5.	Module Self-Tests	17

LIST OF FIGURES

Figure	Title	Page
Figure 2-1.	Luna PCI Cryptographic Module.....	2

LIST OF APPENDICES

Appendix	Title	Page
APPENDIX A.	CRYPTOGRAPHIC ALGORITHMS SUPPORT.....	1
APPENDIX B.	SECURITY POLICY CHECKLIST TABLES	1
APPENDIX C.	LIST OF TERMS, ABBREVIATIONS AND ACRONYMS.....	1



1. INTRODUCTION

1.1. Purpose

This document describes the security policies enforced by SafeNet Inc.'s Luna® PCI Cryptographic Module for Luna® IS (also known as the K5 or Luna IS Cryptographic Module [LISCM]) configured for use in the Luna IS product.

This document applies to Hardware Version VBD-03-0100 and Firmware Versions 5.2.5 and 5.2.6.

1.2. Scope

The security policies described in this document apply to the Trusted Path Authentication (Level 3) configurations of the Luna® PCI Cryptographic Module for Luna® IS only and do not include any security policy that may be enforced by the host appliance or server.

2. SECURITY POLICY MODEL INTRODUCTION

2.1. Functional Overview

The Luna® PCI Cryptographic Module for Luna® IS is a multi-chip embedded hardware cryptographic module in the form of a PCI card that resides within a secure communications appliance. It is contained in its own secure enclosure that provides physical resistance to tampering. The cryptographic boundary of the module is defined to encompass all components inside the secure enclosure on the PCI card. Figure 2-1 depicts the Luna PCI cryptographic module.

The module may be explicitly configured to operate in either FIPS Level 3 mode, or in a non-FIPS mode of operation. Configuration in FIPS mode enforces the use of FIPS-approved algorithms only. Configuration in FIPS Level 3 mode also enforces the use of trusted path authentication. Note that selection of FIPS mode occurs at initialization of the HSM, and cannot be changed during normal operation without zeroizing the module's non-volatile memory.

The cryptographic module is accessed directly (i.e., electrically) via either the Trusted Path PIN Entry Device (PED) serial interface or via the PCI communications interface. The module provides secure key generation and storage for symmetric keys and asymmetric key pairs along with symmetric and asymmetric cryptographic services. Access to key material and cryptographic services for users and user application software is provided indirectly through the host appliance. It provides the ability to manage multiple user definitions and concurrent authentication states. The software on the host that provides the connections to the module presents a logical view of "virtual tokens" or "partitions" to user applications. Each partition must be separately authenticated in order to make it available for use.

This Security Policy is specifically written for the Luna® PCI Cryptographic Module for Luna® IS in a **Trusted Path Authentication (FIPS Level 3)** configuration.





Figure 2-1. Luna PCI Cryptographic Module

2.2. Assets to be Protected

The module is designed to protect the following assets:

1. User-generated private keys,
2. User-generated secret keys,
3. Cryptographic services, and
4. Module security critical parameters.

2.3. Operating Environment

The module is assumed to operate as a key management and cryptographic processing card within a security appliance that may operate in a TCP/IP network environment. The host appliance may be used in an internal network environment when key management security is a primary requirement. It may also be deployed in environments where it is used primarily as a cryptographic accelerator, in which case it will often be connected to external networks. It is assumed that the appliance includes an internal host computer that runs a suitably secured operating system, with an interface for use by locally connected or remote administrators and an interface to provide access to the module's cryptographic functions by application services running on the host computer. It is also assumed that only known versions of the application services are permitted to run on the internal host computer of the appliance.

It is assumed that trained and trustworthy administrators are responsible for the initial configuration and ongoing maintenance of the appliance and the cryptographic module.



It is assumed that physical access to the cryptographic module will be controlled, and that connections will be controlled either by accessing the module via a direct local connection or by accessing it via remote connections controlled by the host operating system and application service.

3. SECURITY POLICY MODEL DESCRIPTION

This section provides a narrative description of the security policy enforced by the module, in its most general form. It is intended both to state the security policy enforced by the module and to give the reader an overall understanding of the security behavior of the module. The detailed functional specification for the module is provided elsewhere.

The security behavior of the cryptographic module is governed by the following security policies:

- Operational Policy
- Identification and Authentication Policy
- Access Control Policy
- Cryptographic Material Management Policy
- Firmware Security Policy
- Physical Security Policy

These policies complement each other to provide assurance that cryptographic material is securely managed throughout its life cycle and that access to other data and functions provided by the product is properly controlled. Configurable parameters that determine many of the variable aspects of the module's behavior are specified by the higher level Operational Policy implemented at two levels: the cryptographic module as a whole and the individual partition. This is described in section 3.1.

The Identification and Authentication policy is crucial for security enforcement and it is described in section 3.4. The access control policy is the main security functional policy enforced by the module and is described in section 3.5, which also describes the supporting object re-use policy. Cryptographic Material Management is described in section 3.6. Firmware security, physical security and fault tolerance are described in sections 3.8 through 3.12.

3.1. Operational Policy

The module employs the concept of the Operational Policy to control the overall behavior of the module and each of the partitions within. At each level, either the module or the partition is assigned a fixed set of "capabilities" that govern the allowed behavior of the module or individual partition. The SO establishes the Operational Policy by enabling/disabling or refining the corresponding policy elements to equate to or to be more restrictive than the pre-assigned capabilities.

The set of configurable policy elements is a proper subset of the corresponding capability set. That is, not all elements of the capability set can be refined. Which of the capability set elements have corresponding policy set elements is pre-determined based on the "personality" of the partition or manufacturing restrictions placed on the module.

There are also several fixed settings that do not have corresponding capability set elements. These are elements of the cryptographic module's behavior that are truly fixed and, therefore, are not subject to configuration by the SO. The specific settings are the following:

- Allow/disallow non-sensitive secret keys – fixed as disallow.
- Allow/disallow non-sensitive private keys – fixed as disallow.
- Allow/disallow non-private secret keys – fixed as disallow.
- Allow/disallow non-private private keys – fixed as disallow.
- Allow/disallow secret key creation through the create objects interface – fixed as disallow.
- Allow/disallow private key creation through the create objects interface – fixed as disallow.



Further, policy set elements can only refine capability set elements to more restrictive values. Even if an element of the policy set exists to refine an element of the capability set, it may not be possible to assign the policy set element to a value other than that held by the capability set element. Specifically, if a capability set element is set to allow, the corresponding policy element may be set to either enable or disable. However, if a capability set element is set to disallow, the corresponding policy element can only be set to disable. Thus, an SO cannot use policy refinement to lift a restriction set in a capability definition.

3.1.1. Module Capabilities

The following is the set of capabilities supported at the module level:

- Module is FIPS validated
- Allow/disallow forcing PIN change.
- Allow/disallow non-FIPS algorithms available.
- Allow/disallow Remote Authentication.
- Allow/disallow cloning.
- Allow/disallow partition groups
- Allow/disallow password authentication. (Disallowed in Level 3 configuration)
- Allow/disallow trusted path authentication. (Allowed in Level 3 configuration)
- Allow/disallow Remote PED operations.
- Allow/disallow masking.
- Allow/disallow off-board storage.
- Allow/disallow SO reset of partition PIN.
- Allow/disallow ECC mechanisms.
- Allow/disallow Korean Digital Signature algorithms.
- Number of failed SO logins allowed before the HSM is zeroized (set to 3, configurable up to 10).
- Allow/disallow network replication (default is disallow).

3.1.2. Partition Capabilities

The following is the set of capabilities supported at the partition level. All capability elements described as “allow/disallow some functionality” are Boolean values where false (or zero) equates to disallow the functionality and true (or one) equates to allow the functionality. The remainder of the elements are integer values of the indicated number of bits.

- Allow/disallow Level 3 operation without a challenge.
- Allow/disallow changing of certain key attributes once a key has been created.
- Allow/disallow incrementing of failed login attempt counter on failed challenge response validation.
- Allow/disallow High Availability (HA).
- Allow/disallow user key management capability.
- Allow/disallow multipurpose keys.
- Allow/disallow operation without RSA blinding.
- Allow/disallow signing operations with non-local keys.
- Allow/disallow private key unwrapping.
- Allow/disallow raw RSA operations (only used for RSA-based key transport purposes).
- Allow/disallow Remote Authentication



- Allow/disallow RSA signing without confirmation
- Allow/disallow secret key unwrapping.
- Allow/disallow secret key wrapping
- Allow/disallow activation.
- Allow/disallow automatic activation.
- Minimum password length must be ≥ 7 .
- Number of failed Partition User logins allowed before partition is locked out/cleared. (The maximum value is 15; the default is 15.)

The following tables summarize the module and partition capabilities, showing the typical capability settings for modules configured as Luna® PCI Cryptographic Module for Luna® IS. An **X** indicates a default capability setting. Grayed-out rows indicate that the corresponding capability setting is never used as a default for a Level 3 Luna module in any configuration.¹

Table 3-1 Module Capabilities and Policies

Description	Capability	IS	Policy	Comments
Non-FIPS algorithms available	Allow	X	Enable	SO can configure the policy to enable or disable the availability of non-FIPS algorithms at the time the HSM is initialized.
			Disable	
	Disallow		Disable	The HSM must operate using FIPS-approved algorithms only. Must be disabled in FIPS mode
Password authentication	Allow		Enable	SO can configure the policy to enable or disable the use of passwords without trusted path for authentication.
			Disable	
Disallow	X		Disable	The HSM must operate using the trusted path and module-generated secrets for authentication.
Trusted path authentication	Allow	X	Enable	SO can configure the policy to enable or disable the use of the trusted path and module-generated secrets for authentication.
			Disable	
Disallow			Disable	The HSM must operate using passwords without trusted path for authentication. ²
Partition groups	Allow	X	Enable	SO can configure the policy to enable or disable groups of partitions, such that members of a group share the same PED authentication data and configuration options.
			Disable	
Disallow			Disable	The module cannot have groups of partitions.
Cloning	Allow	X	Enable	SO can configure the policy to enable or disable the availability of the cloning function for the HSM as a whole.
			Disable	
Disallow			Disable	The HSM must operate without cloning.
Masking	Allow	X	Enable	SO can configure the policy to enable or disable the availability of the masking function for the HSM as a whole.
			Disable	
Disallow			Disable	The HSM must operate without masking.
Off-board Storage	Allow	X	Enable	Off-board storage is used for backup purposes in the Luna® PCI Cryptographic Module for Luna® IS. The SO can enable or disable the use of off-board storage.
			Disable	
Disallow			Disable	Off-board storage is not allowed.
ECC mechanisms available	Allow	X	Enable	This capability is set prior to shipment to the customer. It controls the availability of ECC mechanisms.
			Disable	
	Disallow		Disable	ECC mechanisms are not available.

¹ In this Security Policy, there is only one module configuration considered for Luna PCI for Luna IS. Other Luna Security Policies include several different module configurations and the grayed-out rows indicate settings that are never used in any module configurations.

² One and only one means of authentication ("user password" or "trusted path") must be enabled by the policy. Therefore, either one or both of the authentication capabilities must be allowed and, if one of the capabilities is disallowed or the policy setting disabled, then the policy setting for the other must be enabled.



Description	Capability	IS	Policy	Comments
Partition reset	Allow	X	Enable	SO can configure the policy to enable a partition to be reset if it is locked as a result of exceeding the maximum number of failed login attempts.
			Disable	
Network Replication	Allow		Enable	SO can configure the policy to enable the replication of the module's key material over the network to a second module.
			Disable	
Force user PIN change	Allow	X	Enable	This capability is set prior to shipment to the customer. If enabled, it forces the user to change PIN upon first login.
			Disable	
Remote authentication	Allow	X	Enable	This capability is set prior to shipment to the customer. It allows the use of remote authentication.
			Disable	
Remote PED operations	Allow	X	Enable	This capability is set prior to shipment to the customer. It allows the use of Remote PED operations. The SO can configure according to the local policy.
			Disable	
	Disallow		Disable	Remote PED operations cannot be enabled for the module.

Table 3-2 Partition Capabilities and Policies

Description	Prerequisite	Capability	IS	Policy	Comments
Level 3 operation without a challenge	Trusted path authentication enabled	Allow	X	Enable	SO can configure the policy to enable Level 3 login using the PED trusted path only, with no challenge-response validation required. Must be disabled if either activation or auto-activation is enabled
				Disable	
User key management capability ³	Trusted path authentication enabled, Level 3 operation without a challenge disabled	Allow	X	Enable	SO can configure the policy to enable the normal PKCS #11 user role to perform key management functions. If enabled, the Crypto Officer key management functions are available. If disabled, only the Crypto User role functions are accessible.
				Disable	
Count failed challenge-response validations	Trusted path authentication enabled	Allow	X	Enable	SO can configure the policy to count failures of the challenge-response validation against the maximum login failures. Must be enabled if either activation or auto-activation is enabled
				Disable	
		Disallow		Disable	Failures of the challenge-response validation are not counted against the maximum login failures.

³ This capability/policy is intended to offer customers a greater level of control over key management functions. By disabling the policy, the Security Officer places the partition into a state in which the key material is locked down and can only be used by connected applications, i.e., only Crypto User access is possible.



Description	Prerequisite	Capability	IS	Policy	Comments
Activation	Trusted path authentication enabled	Allow	X	Enable	SO can configure the policy to enable the authentication data provided via the PED trusted path to be cached in the module, allowing all subsequent access to the partition, after the first login, to be done on the basis of challenge-response validation alone.
				Disable	
		Disallow		Disable	PED trusted path authentication is required for every access to the partition.
Auto-activation	Trusted path authentication enabled	Allow	X	Enable	SO can configure the policy to enable the activation data to be stored in encrypted form, allowing the partition to resume its authentication state after a re-start. This is intended primarily to allow partitions to automatically re-start operation when the appliance returns from a power outage.
				Disable	
		Disallow		Disable	Activation data cannot be cached.
High Availability	N/A	Allow	X	Enable	SO can configure the policy to enable the use of the High Availability feature.
				Disable	
		Disallow		Disable	High Availability cannot be enabled.
Multipurpose keys	N/A	Allow	X	Enable	SO can configure the policy to enable the use of keys for more than one purpose, e.g., an RSA private key could be used for digital signature and for decryption.
				Disable	
		Disallow		Disable	Keys can only be used for a single purpose.
Change attributes	N/A	Allow	X	Enable	SO can configure the policy to enable changing key attributes.
				Disable	
		Disallow		Disable	Key attributes cannot be changed.
Operate without RSA blinding	N/A	Allow	X	Enable	SO can configure the use of blinding mode for RSA operations. Blinding mode is used to defeat timing analysis attacks on RSA digital signature operations, but it also imposes a significant performance penalty on the signature operations.
				Disable	
		Disallow		Disable	Blinding mode is not used for RSA operations.
Signing with non-local keys	N/A	Allow	X	Enable	SO can configure the ability to sign with externally-generated private keys that have been imported into the partition.
				Disable	
		Disallow		Disable	Externally-generated private keys cannot be used for signature operations.
Raw RSA operations	N/A	Allow	X	Enable	SO can configure the ability to use raw (no padding) format for RSA operations.
				Disable	
		Disallow		Disable	Raw RSA cannot be used.
Private key wrapping	N/A	Allow		Enable	SO can configure the ability to wrap private keys for export.
				Disable	
		Disallow	X	Disable	Private keys cannot be wrapped and exported from the partition.



Description	Prerequisite	Capability	IS	Policy	Comments
Private key unwrapping	N/A	Allow	X	Enable	SO can configure the ability to unwrap private keys and import them into the partition.
				Disable	
Secret key wrapping	N/A	Allow	X	Enable	SO can configure the ability to wrap secret keys and export them from the partition.
				Disable	
Secret key unwrapping	N/A	Allow	X	Enable	SO can configure the ability to unwrap secret keys and import them into the partition.
				Disable	
Private key cloning	Cloning enabled, Trusted path authentication enabled	Allow		Enable	SO can configure the ability to clone private keys from one partition to another.
			Disable		
Secret key cloning	Cloning enabled, Trusted path authentication enabled	Allow		Enable	SO can configure the ability to clone secret keys from one partition to another.
			Disable		
Private key masking	Masking enabled	Allow	X	Enable	SO can configure the ability to mask private keys for storage outside the partition.
				Disable	
Secret key masking	Masking enabled	Allow	X	Enable	SO can configure the ability to mask secret keys for storage outside the partition.
				Disable	
Remote Authentication	Remote Authentication enabled at the module level	Allow	X	Enable	SO can configure the ability to use remote authentication for the partition.
				Disable	
Minimum password length	User password authentication enabled	7-16 characters		Configurable	Minimum password length must always be ≥ 7 .
Number of failed Partition User logins allowed	N/A	15		Configurable	The SO can configure. Default is 15; maximum value is 15.
RSA signature confirmation	N/A	Allow	X	Enable	SO can configure internal RSA signature verification in the module before returning the signature to the caller.
				Disable	
		Disallow		Disable	Internal RSA signature verification cannot be turned on.

3.2. FIPS-Approved Mode

The SO controls operation of the module in FIPS-approved mode, as defined by FIPS PUB 140-2, by enabling or disabling the appropriate Module Policy settings (assuming each is allowed at the Module Capability level). To operate in FIPS-approved mode, the following policy settings are required:

- “Non-FIPS Algorithms Available” must be disabled.

Additionally, for operation at **FIPS Level 3**:

- “Trusted path authentication” must be enabled (implies that password authentication is disallowed or disabled),
- “Level 3 operation without a challenge” must be disabled if activation or auto-activation is enabled, and
- “Count failed challenge – response validations” must be enabled if activation or auto-activation is enabled.
- Raw RSA operations must only be used for key transport in FIPS mode.

The policy settings for “Trusted path authentication” may also be configured in the case where “Non-FIPS Algorithms Available” has been enabled.

If the SO selects policy options (i.e., enables “Non-FIPS Algorithms Available”) that would place the module in a mode of operation that is not approved, a warning is displayed and the SO is prompted to confirm the selection. The SO can determine FIPS mode of operation by matching the displayed capability and policy settings to those described in Sections 3.1 and 3.2.

3.3. Description of Operator, Subject and Object

3.3.1. Operator

An operator is defined as an entity that acts to perform an operation on the module. An operator may be directly mapped to a responsible individual or organization, or it may be mapped to a composite of a responsible individual or organization plus an agent (application program) acting on behalf of the responsible individual or organization.

In the case of a Certification Authority (CA), for example, the organization may empower one individual or a small group of individuals acting together to operate the cryptographic module as part of the company’s service. The operator might be that individual or group, particularly if they are interacting with the module locally. The operator might also be the composite of the individual or group, who might still be present locally to the module (particularly for activation purposes, see section 3.4.2), plus the CA application running on a network-attached host computer.

3.3.2. Roles

The Luna® PCI Cryptographic Module for Luna® IS supports three authenticated operator roles: Crypto User and Crypto Officer for each partition (collectively called the Partition Users), plus the Security Officer at the module level. It also supports one unauthenticated operator role, the Public User, primarily to permit access to status information and diagnostics before authentication.

The SO is a privileged role, which exists only at the module level, whose primary purpose is to initially configure the module for operation and to perform security administration tasks such as partition creation.



The Luna® PCI Cryptographic Module for Luna® IS can be configured to support many individual user partitions within one group partition. The Crypto Officer is the key management role for each partition and the Crypto User is an optional read-only role that limits the operator to performing cryptographic operations only.

For an operator to assume any role other than Public User, the operator must be identified and authenticated. The following conditions must hold in order to assume one of the authenticated roles:

- No operator can assume the Crypto Officer, Crypto User or Security Officer role before identification and authentication;
- No identity can assume either the Crypto Officer or Crypto User plus the Security Officer role.

The SO can create the Crypto User role by creating a challenge value for the Crypto User. In the case of a partition that supports the Crypto Officer and Crypto User roles, the Security Officer can limit access to only the Crypto User role by disabling the “User Key Management” (see Table 3-1) policy.

3.3.3. Account Data

The module maintains the following Partition User (which can include both the Crypto Officer and Crypto User role for the partition⁴) and SO account data:

- Partition ID or SO ID number.
- Partition User encrypted or SO encrypted authentication data (checkword).
- Partition User authentication challenge secret (one for each role, as applicable).
- Partition User locked out flag.

The ability to manipulate the account data is restricted to the SO and the Partition User. The specific restrictions are as described below:

1. Only the Security Officer role can create (initialize) and delete the following security attributes:
 - Partition ID.
 - Checkword.
2. If Partition reset is allowed and enabled, the SO role only can modify the following security attribute:
 - Locked out flag for Partition User.
3. Only the Partition User can modify the following security attribute:
 - Checkword for Partition User.
4. Only the Security Officer role can change the default value, query, modify and delete the following security attribute:
 - Checkword for Security Officer.

⁴ A Partition effectively represents an identity within the module.

3.3.4. Subject

For purposes of this security policy, the subject is defined to be a module session. The session provides a logical means of mapping between applications connecting to the module and the processing of commands within the module. Each session is tracked by the Session ID, the Partition ID and the Access ID, which is a unique ID associated with the application's connection. It is possible to have multiple open sessions with the module associated with the same Access ID/Partition ID combination. It is also possible for the module to have sessions opened for more than one Partition ID or have multiple Access IDs with sessions opened on the module. Applications running on remote host systems that require data and cryptographic services from the module must first connect via the communications service within the appliance, which will establish the unique Access ID for the connection and then allow the application to open a session with one of the partitions within the module. A local application (e.g., command line administration interface) will open a session directly with the appropriate partition within the module without invoking the communications service.

3.3.5. Operator – Subject Binding

An operator must access a partition through a session. A session is opened with a partition in an unauthenticated state and the operator must be authenticated before any access to cryptographic functions and Private objects within the partition can be granted. Once the operator is successfully identified and authenticated, the session state becomes authenticated and is bound to the Partition User represented by the Partition ID, in the Crypto Officer or Crypto User role. Any other sessions opened with the same Access ID/Partition ID combination will share the same authentication state and be bound to the same Partition User.

3.3.6. Object

An object is defined to be any formatted data held in volatile or non-volatile memory on behalf of an operator. For the purposes of this security policy, the objects of primary concern are private (asymmetric) keys and secret (symmetric) keys.

3.3.7. Object Operations

Object operations may only be performed by a Partition User. The operations that may be performed are limited by the role (Crypto Officer or Crypto User) associated with the user's login state, see section 3.5. New objects can be made in several ways. The following list identifies operations that produce new objects:

- Create,
- Copy,
- Generate,
- Unwrapping,
- Derive.

Existing objects can be modified and deleted. The values of a subset of attributes can be changed through a modification operation. Objects can be deleted through a destruction operation. Constant operations do not cause creation, modification or deletion of an object. These constant operations include:

- Query an object's size;
- Query the size of an attribute;
- Query the value of an attribute;
- Use the value of an attribute in a cryptographic operation;
- Search for objects based on matching attributes;



- Cloning an object;
- Wrapping an object; and
- Masking and unmasking an object.

Secret keys and private keys are always maintained as Sensitive objects and, therefore, they are permanently stored with the key value encrypted to protect its confidentiality. Operators are not given direct access to key values for any purpose.

3.4. Identification and Authentication

3.4.1. Authentication Data Generation and Entry

The module generates the authentication secret as a 48-byte random value and, if Activation is enabled for the partition, as a challenge secret for the Partition User, identified to the module by the Partition ID number as described in section 3.3.3. The authentication secret(s) are provided to the operator via a physically separate trusted path, described in section 3.4.2, and must be entered by the operator via the trusted path and via a logically separate trusted channel (in the case of the response based on the challenge secret) during the login process. If a Partition is created with Crypto Officer and Crypto User roles, a separate challenge secret is generated for each role.

When a Group Partition is used, the password (or passwords if the Crypto Officer and Crypto User roles are used) for each individual key container⁵ is established by the user when the key container is initialized. The password is used by the login process in the same challenge-response scheme as the one used for partition authentication.

3.4.2. Trusted Path

User authentication is a two-stage process. The first stage is termed “Activation” and is performed using the Luna PED. Activation requires the transmission to the cryptographic module of the Black iKey data combined with the optional PIN through the trusted path. Once Activation has been performed, the partition data is ready for use within the cryptographic module. Access to key material and cryptographic services, however, is not allowed until the second stage of authentication, equivalent to “User Login”, has been performed. This typically requires the input of a partition’s challenge secret as part of a login operation. The challenge secret is combined with a random one-time challenge from the module to form the response. The encrypted one-time response is returned to the cryptographic module where it is verified to confirm the “User Login”.

However, for SO authentication and for user authentication when the settings of the Partition Policy disable the use of challenge/response authentication for login to a partition⁶, the presentation of the iKey data (i.e., equivalent to Activation) is all that is required to complete authentication.

3.4.2.1. Remote PED Operation

The user has the option of operating the PED in the conventional manner (i.e., locally connected to the HSM) or remotely, connected to a management workstation via USB. Remote PED operation extends the physical trusted path connection by the use of a protocol that authenticates both the remote PED and the HSM and establishes a one-time AES key to encrypt the communications between the HSM and the remote PED. Once secure communications have been established, all interactions between the HSM, PED and iKeys are performed in exactly the same way as they would be when locally connected.

The logical path between the HSM and the remote PED is secured in the manner described below.

⁵ In this case, the key container or “sub-partition” represents an identity within the module.

⁶ Challenge/response authentication might, for example, be disabled in a case where both the cryptographic module and the attached application server are located within a physically secured environment and the user is always required to be physically present to start the application and authenticate to the cryptographic module via the PED.

At the time it is initialized, the HSM generates a random 256 bit secret known as the Remote PED Vector (RPV), stores it in its secure parameters area and writes it to the “Orange” iKey, also known as the Remote PED Key (RPK).

To establish the secure connection, the RPK must be inserted into the PED. The PED extracts the RPV, and the PED and the HSM then participate in an ephemeral Diffie-Hellman key agreement session. The derived shared secret is then XORed with the RPV to produce the key to be used for the session. An exchange of encrypted random nonces is performed to authenticate both ends of the transmission. All traffic between the PED and the HSM is encrypted using AES 256.

3.4.3. M of N Authentication

The Luna PCI cryptographic module when configured for use with Luna IS supports the use of an **M of N secret sharing** authentication scheme. M of N authentication provides the capability to enforce multi-person integrity over SO operations and activation of each partition.

The M of N capability is based on Shamir’s threshold scheme. The Luna cryptographic module splits the randomly-generated authentication data into “N” pieces, known as splits, and stores each split on an iKey. Any “M” of these “N” splits must be transmitted to the Luna cryptographic module by inserting the corresponding iKeys into the Luna PED in order to reconstruct the original secret.

When the M of N set is distributed to recipients outside the module, the split data is contained in M of N vectors. A vector may contain one or more splits depending on the weight assigned at the time of generation. For example, in the case of a three-of-five activation setting, it may be desired for A to receive the equivalent of two splits whereas B, C and D only receive one each for a total of five. Each vector carries the identifier of the M of N set to which it belongs.

3.4.4. Limits on Login Failures

The module also implements a maximum login attempts policy. The policy differs for an SO authentication data search and a Partition User authentication data search.

In the case of an SO authentication data search:

- If three (3)⁷ consecutive SO logon attempts fail, the module is zeroized.

In the case of a Partition User authentication data search, one of two responses will occur, depending on the partition policy:

1. If “Partition reset” is Allowed and Enabled, then if “n” (“n” is set by the SO at the time the HSM is initialized) consecutive operator logon attempts fail, the module flags the event in the Partition User’s account data, locks the Partition User and clears the volatile memory space. The SO must unlock the partition in order for the Partition User to resume operation.
2. If “Partition reset” is not Allowed or not Enabled, then if “n” consecutive Partition User logon attempts fail, the module will erase the partition. The SO must delete and re-create the partition. Any objects stored in the partition, including private and secret keys, are permanently erased.

3.5. Access Control

The Access Control Policy is the main security function policy enforced by the module. It governs the rights of a subject to perform privileged functions and to access objects stored in the module. It covers the object operations detailed in section 3.3.7.

A subject’s access to objects stored in the module is mediated on the basis of the following subject and object attributes:

⁷ Configurable to a maximum of 10; default is 3.

- Subject attributes:
 - Session ID
 - Access ID and Partition ID associated with session
 - Session authentication state (binding to authenticated Partition identity and role)
- Object attributes:
 - **Owner.** A Private object is owned by the Partition User associated with the subject that produces it. Ownership is enforced via internal key management.
 - **Private.** If True, the object is Private. If False, the object is Public.
 - **Sensitive.** If True, object is Sensitive. If False, object is Non-Sensitive.
 - **Extractable⁸.** If True, object may be extracted. If False, object may not be extracted.
 - **Modifiable.** If True, object may be modified. If False, object may not be modified.

Objects are labeled with a number corresponding to their partition and are only accessible by a subject associated with the owning Partition ID. Only generic data and certificate objects can be non-sensitive. Sensitive objects are encrypted using the partition’s secret key to prevent their values from ever being exposed to external entities. Key objects are always created as Sensitive objects and can only be used for cryptographic operations by a logged in Partition User. Key objects that are marked as extractable may be exported from the module using the Wrap operation if allowed and enabled in the partition’s policy set. Table 3-3 summarizes the object attributes used in Access Control Policy enforcement.

Table 3-3 Object Attributes Used in Access Control Policy Enforcement

Attribute	Values	Impact
PRIVATE	TRUE – Object is private to (owned by) the operator identified as the Access Owner when the object is created.	Object is only accessible to subjects (sessions) bound to the operator identity that owns the object.
	FALSE – Object is not private to one operator identity.	Object is accessible to all subjects associated with the partition in which the object is stored.
SENSITIVE	TRUE – Attribute values representing plaintext key material are not permitted to exist (value encrypted).	Key material is stored in encrypted form.
	FALSE – Attribute values representing plaintext data are permitted to exist.	Plaintext data is stored with the object and is accessible to all subjects otherwise permitted access to the object.
MODIFIABLE	TRUE – The object’s attribute values may be modified.	The object is “writeable” and its attribute values can be changed during a copy or set attribute operation.
	FALSE – The object’s values may not be modified.	The object can only be read and only duplicate copies can be made.
EXTRACTABLE	TRUE – Key material stored with the object may be extracted from the Luna® PCI Cryptographic Module for Luna® IS using the Wrap operation.	The ability to extract a key permits sharing with other crypto-modules and archiving of key material.
	FALSE – Key material stored with the object may not be extracted from the Luna IS cryptographic module.	Keys must never leave the module’s control.

⁸Extract means to remove the key from the control of the module. This is typically done using the Wrap operation.



The module does not allow any granularity of access other than owner or non-owner (i.e., a Private object is only accessible by one Partition User. It cannot be accessible by two Partition Users and restricted to other Partition Users). Ownership of a Private object gives the owner access to the object through the allowed operations but does not allow the owner to assign a subset of rights to other operators. Allowed operations are those permitted by the HSM and Partition Capability and Policy settings.

The policy is summarized by the following statements:

- A subject may perform an allowed operation on an object if the object is in the partition with which the subject is associated and one of the following two conditions holds:
 1. The object is a “Public” object, i.e., the PRIVATE attribute is FALSE, or
 2. The subject is bound to the Partition User that owns the object.
- Allowed operations are those permitted by the object attribute definitions within the following constraints:
 1. A Partition User in the Crypto User role has access to only the User operations, and
 2. The restrictions imposed by the HSM and Partition Capability and Policy settings.

3.5.1. Object Re-use

The access control policy is supported by an object re-use policy. The object re-use policy requires that the resources allocated to an object be cleared of their information content before they are re-allocated to a different object.

3.5.2. Privileged Functions

The module shall restrict the performance of the following functions to the SO role only:

- Module initialization
- Partition creation and deletion
- Configuring the module and partition policies
- Module zeroization
- Firmware update

3.6. Cryptographic Material Management

Cryptographic material (key) management functions protect the confidentiality of key material throughout its life-cycle. The FIPS PUB 140-2 approved key management functions provided by the module are the following:

- (1) Pseudo random number generation in accordance with ANSI X9.31, Appendix A2.4.
- (2) Cryptographic key generation in accordance with the following indicated standards:
 - a. RSA 1024-4096 bits key pairs in accordance with FIPS PUB 186-2.
 - b. TDES 112, 168 bits (FIPS PUB 46-3, ANSI X9.52).
 - c. AES 128, 192, 256 bits (FIPS PUB 197).
 - d. DSA 1024 bits key pairs in accordance with FIPS PUB 186-2.
- (3) Secure key storage and key access following the PKCS #11 standard.



- (4) Destruction of cryptographic keys is performed in one of three ways as described below in accordance with the PKCS #11 and FIPS PUB 140-2 standards:
- a. An object on the Luna® PCI Cryptographic Module for Luna® IS that is destroyed using the PKCS #11 function `C_DestroyObject` is marked invalid and its attributes are zeroized (all bits set to zero). The object memory location (flash or RAM) remains occupied by the zeroized object until such time as it is re-allocated for additional data on the Luna® PCI Cryptographic Module for Luna® IS.
 - b. Objects on the Luna® PCI Cryptographic Module for Luna® IS that are destroyed as a result of authentication failure are zeroized (all flash blocks in the Partition User's memory turned to 1's). If it is an SO authentication failure, all flash blocks used for key and data storage on the Luna® PCI Cryptographic Module for Luna® IS are zeroized.
 - c. Objects on the Luna® PCI Cryptographic Module for Luna® IS that are destroyed through `C_InitToken` (the SO-accessible command to initialize the Luna® PCI Cryptographic Module for Luna® IS available through the API) are zeroized, along with the rest of the flash memory being used by the SO and Partition Users.

Keys are always stored as secret key or private key objects with the Sensitive attribute set. The key value is, therefore, stored in encrypted form using the owning Partition User's secret key. Access to keys is never provided directly to a calling application. A handle to a particular key is returned that can be used by the application in subsequent calls to perform cryptographic operations.

Private key and secret key objects may be imported into the module using the Unwrap, Unmask (if enabled at the HSM and partition level) or Derive operation under the control of the Access Control Policy. Any externally-set attributes of keys imported in this way are ignored by the module and their attributes are set by the module to values required by the Access Control Policy.

3.7. Cryptographic Operations

Because of its generic nature, the module firmware supports a wide range of cryptographic algorithms and mechanisms. The approved cryptographic functions and algorithms that are relevant to the FIPS 140-2 validation are the following:

- (1) Symmetric encryption/decryption (wrap/unwrap): TDES 112, 168 bits (FIPS PUB 46-3, ANSI X9.52).
- (2) Symmetric encryption/decryption (wrap/unwrap): AES 128, 192, 256 bits (FIPS PUB 197).
- (3) Asymmetric key wrap/unwrap: RSA 1024-4096 (PKCS #1 V1.5)
- (4) Signature generation/verification: RSA 1024-4096 bits (PKCS #1 V1.5) with SHA-1, SHA-224, SHA-256, SHA-384, SHA-512 (FIPS PUB 180-2), RSA 1024-4096 bits (PSS) with SHA-1, SHA-224, SHA-256, SHA-384, SHA-512 (FIPS PUB 180-2), RSA 1024-4096 bits (X9.31) with SHA-1, DSA 1024 bits (FIPS PUB 186-2) with SHA-1, ECDSA (ANSI X9.62) with SHA-1.
- (5) Hash generation SHA-1, SHA-224, SHA-256, SHA-384, SHA-512 (FIPS PUB 180-2).
- (6) Keyed hash generation HMAC using SHA-1, SHA-224, SHA-256, SHA-384, SHA-512 (FIPS PUB 198).
- (7) Message authentication TDES MAC (FIPS PUB 113)
- (8) Random number generation (ANSI X9.31 A2.4).



Algorithm Validation Certificates
AES (Certificate #510, Certificate #910 and Certificate # 913)
DSA (Certificate #320 and Certificate #326)
ECDSA (Certificate #110 and Certificate #112) – Only NIST Recommended Curves
HMAC: SHA-1, SHA-224, SHA-256, SHA-384, SHA-512 (Certificate #507 and Certificate #509)
RNG (Certificate #522 and Certificate #523)
RSA (Certificate #442, Certificate #444, Certificate #454 and Certificate #455)
SHA-1, SHA-224, SHA-256, SHA-384, SHA-512 (Certificate #898 and Certificate #900)
TDES (Certificate #520, Certificate #728 and Certificate #738)
TDES MAC (Vendor Affirmed; Certificate #520, Certificate #728 and Certificate #738)

Table 3-4. Algorithm Validation Certificates

3.8. Self-tests

The module provides self-tests on power-up and on request to confirm the firmware integrity, and to check the random number generator and each of the implemented cryptographic algorithms.

Test	When Performed	Indicator
Firmware CRC by boot block prior to firmware start	Power-on	Module halt ⁹
Firmware SHA-1	Power-on	Module halt
Known-Answer Tests (KATs) for all approved functions (Section 3.7)	Power-on / Request	Module halt / Error - Halt
RNG continuous tests	Continuous	Error - Halt
Pair-wise consistency tests (asymmetric key pairs)	On generation	Error
Firmware load test	On firmware update load	Error – module will continue with existing firmware

Table 3-5. Module Self-Tests

3.9. Firmware Security

The Firmware Security Policy assumes that any firmware images loaded in conformance with the policy have been verified by SafeNet to ensure that the firmware will function correctly. The policy applies to initial firmware loading and subsequent firmware updates.

The module shall not allow external software¹⁰ to be loaded inside its boundary. Only properly formatted firmware may be loaded. The communication of initial or updated firmware to a target module is initiated by a SafeNet module dedicated to that function. Firmware shall be digitally signed using the SafeNet Manufacturing signature key and encrypted using a secret key that may be derived by the receiving module for decryption. The unencrypted firmware must not be visible outside the module before, during and after the loading operation.

⁹ Details of the failure can be obtained from the dual-port following a module halt.

¹⁰ External software means any form of executable code that has been generated by anyone other than SafeNet and has not been properly formatted and signed as a legitimate SafeNet firmware image.



The firmware shall provide mechanisms to ensure its own integrity and to ensure the integrity of any permanent security-critical data stored within the module.

3.10. Physical Security

The Luna® PCI Cryptographic Module for Luna® IS is a multi-chip embedded module as defined by FIPS PUB 140-2 section 4.5. It is enclosed in a strong enclosure that provides tamper-evidence. Any tampering that might compromise the module's security is detectable by visual inspection of the physical integrity of the module. The enclosure covers are bonded to the circuit card assembly and any attempt to remove either of the covers will result in significant damage to the card, rendering the module inoperable.

The module's enclosure is opaque to resist visual inspection of the device design, physical probing of the device and attempts to access sensitive data on individual components of the device.

The only plaintext Critical Security Parameter (CSP) stored inside the module is the Token Variable Key (TVK), which is used to implement the auto-activation feature. If that feature is used, the TVK is stored in battery-backed RAM, which is zeroized in the event of a tamper detection – either from the external tamper signal or removal of the card from the PCI slot.

3.11. EMI/EMC

The module conforms to FCC Part 15 Class B requirements for home use.

3.12. Fault Tolerance

If power is lost to the module for whatever reason, the module shall, at a minimum, maintain itself in a state that it can be placed back into operation when power is restored without compromise of its functionality or permanently stored data.

The module shall maintain its secure state¹¹ in the event of data input/output failures. When data input/output capability is restored the module will resume operation in the state it was prior to the input/output failure.

3.13. Mitigation of Other Attacks

Timing attacks are mitigated directly by the module through the use of hardware accelerator chips for modular exponentiation operations. The use of hardware acceleration ensures that all RSA signature operations complete in very nearly the same time, therefore making the analysis of timing differences irrelevant. RSA blinding may also be selected as an option to mitigate this type of attack.

¹¹ A secure state is one in which either the Luna IS cryptographic module is operational and its security policy enforcement is functioning correctly, or it is not operational and all sensitive material is stored in a cryptographically protected form on the Luna IS cryptographic module.

APPENDIX A. CRYPTOGRAPHIC ALGORITHMS SUPPORT

FIPS-approved algorithms are shown in bold lettering.

Random Number Generation

- **ANSI X9.31 Appendix A, para 2.4** (uses non-approved HRNG as source of seed data)

Encrypt/Decrypt:

- **TDES-ECB**
- **TDES-CBC**
- **AES-ECB**
- **AES-CBC**
- DES-ECB
- DES-CBC
- RC2-ECB
- RC2-CBC
- RC4
- RC5-ECB
- RC5-CBC
- CAST-ECB
- CAST-CBC
- CAST3-ECB
- CAST3-CBC
- CAST5-ECB
- CAST5-CBC
- RSA X-509
- SEED

Digest:

- **SHA-1**
- **SHA-224**
- **SHA-256**
- **SHA-384**
- **SHA-512**
- MD2
- MD5
- HAS-160

Sign/Verify:

- **RSA-1024-4096 X9.31**
- **RSA-1024-4096 PKCS #1 V1.5**
- **RSA-1024-4096 PSS with SHA-1, SHA-224, SHA-256, SHA-384, SHA-512**
- **DSA 1024**
- **ECDSA**
- **TDES-MAC**
- **HMAC-SHA1**
- **HMAC-SHA-224**
- **HMAC-SHA-256**
- **HMAC-SHA-384**
- **HMAC-SHA-512**
- AES MAC
- DES-MAC
- RC2-MAC
- RC5-MAC
- CAST-MAC
- CAST3-MAC
- CAST5-MAC
- SSL3-MD5-MAC
- SSL3-SHA1-MAC
- HMAC-MD5
- KCDSA



Generate Key:

- **2Key TDES**
- **3Key TDES**
- **AES 128, 192, 256 bits**
- DES
- RC2
- RC4
- RC5
- CAST
- CAST3
- CAST5
- SEED
- PBE-MD2-DES
- PBE-MD5-DES
- PBE-MD5-CAST
- PBE-MD5-CAST3
- PBE-SHA-1-CAST5
- GENERIC-SECRET
- SSL PRE-MASTER

Generate Key Pair:

- **RSA-1024 – 4096 X9.31 and PKCS #1**
- **DSA-1024**
- **ECDSA (NIST curves)**
- DH-1024 - provides 80-bits of encryption strength
- KCDSA

Wrap Symmetric Key Using Symmetric Algorithm:

- **TDES-ECB**
- **AES ECB**
- RC2-ECB
- CAST-ECB
- CAST3-ECB
- CAST5-ECB

Wrap Symmetric Key Using Asymmetric Algorithm:

- **RSA-1024 - provides 80-bits of encryption strength**
- **RSA-2048 - provides 112-bits of encryption strength**
- **RSA 4096 - provides 150-bits of encryption strength**

Wrap Asymmetric Key Using Symmetric Algorithm:

- **TDES-CBC**
- **AES-CBC**

Unwrap Symmetric Key With Symmetric Algorithm:

- **TDES-ECB**
- **AES ECB**
- RC2-ECB
- CAST-ECB
- CAST3-ECB
- CAST5-ECB

Unwrap Symmetric Key With Asymmetric Algorithm:

- **RSA-1024**
- **RSA-2048**
- **RSA-4096**

Unwrap Asymmetric Key With Symmetric Algorithm:

- **TDES-CBC**
- **AES-CBC**
- CAST-CBC
- CAST3-CBC
- CAST5-CBC



APPENDIX B. SECURITY POLICY CHECKLIST TABLES

Table B-1 Roles and Required Identification and Authentication

Role	Type of Authentication	Authentication Data
Security Officer	Identity-based	Level 3 – Authentication token (iKey – one or optional split key) plus optional PED PIN
Crypto Officer	Identity-based ¹²	Level 3 – Authentication token (iKey – one or optional split key) plus optional PED PIN, plus optional Challenge Secret for the role ¹³
Crypto User	Identity-based	Level 3 – Authentication token (iKey – one or optional split key) plus optional PED PIN, plus optional Challenge Secret for the role
Public User	Not required	N/A

Table B-2 Strengths of Authentication Mechanisms

Authentication Mechanism	Strength of Mechanism
iKey (Level 3) plus PIN	48 byte random authentication data stored on iKey plus PIN entered via PED key pad (if PED PIN is used, minimum length is 4 digits)
Challenge Secret (Level 3)	75 random bits represented as 16 character string

Table B-3 Services Authorized for Roles

Role	Authorized Services
Security Officer	Show Status, Self-test, Zeroize Module, Initialize Module, Configure Module Policy, Create Partition, Configure Partition Policy, Firmware Update, HSM Backup and Restore
Crypto Officer	Show Status, Self-test, Key and Key Pair Generation, Symmetric Encrypt/Decrypt, Asymmetric Signature/Verification, Symmetric & Asymmetric Key Wrap/Unwrap, Store Data Object, Read Data Object, Partition Backup and Restore
Crypto User	Show Status, Self-test, Symmetric Encrypt/Decrypt, Asymmetric Signature/Verification, Store Data Object, Read Data Object
Public User	Show Status, Self-test, Store Public Data Object, Read Public Data Object

¹² The Crypto Officer and Crypto User both apply to the same partition, i.e., identity. They are distinguished by different challenge values representing the two different roles.

¹³ If activation or auto-activation is enabled, challenge secret is required in FIPS mode



Table B-4 Access Rights within Services

Service	Cryptographic Keys and CSPs	Role	Type(s) of Access
Show Status ¹⁴	N/A	All	N/A
Self-test	N/A	All	N/A
Initialize Module	Authentication data via trusted path	SO	Write – SO authentication data
Firmware Update	MVK ¹⁵	SO	Use, Write (firmware only)
Configure Module Policy	Authentication data via trusted path	SO	Use ¹⁶
Create Partition	Authentication data via trusted path	SO	Write – User authentication data
Configure Partition Policy	Authentication data via trusted path	SO	Use
Key and Key Pair Generation	Symmetric keys, asymmetric key pairs	Crypto Officer	Write
Symmetric Key Wrap/ Unwrap	Symmetric with RSA Symmetric with Symmetric ECB mode	Crypto Officer	Use, Write
Asymmetric Key Wrap/ Unwrap	Asymmetric with Symmetric CBC mode	Crypto Officer	Use, Write
Symmetric Key Mask/ Unmask	Symmetric with AES 256	Crypto Officer	Use, Write
Asymmetric Key Mask/ Unmask	Symmetric with AES 256	Crypto Officer	Use, Write
Backup / Restore	Symmetric keys, asymmetric key pairs	Crypto Officer	Transfer ¹⁷
Symmetric Encrypt/Decrypt	Symmetric keys	Crypto Officer, Crypto User	Use
Asymmetric Signature	RSA, DSA private keys	Crypto Officer, Crypto User	Use
Asymmetric Verification	RSA, DSA public keys	Crypto Officer, Crypto User	Use
Store Data Object	Non-cryptographic data	Crypto Officer, Crypto User, Public User ¹⁸	Write
Read Data Object	Non-cryptographic data	Crypto Officer, Crypto User, Public User ¹⁸	Read
Zeroize	Authentication data, symmetric keys, asymmetric key pairs	SO	Write, Erase

Table B-5 Keys and Critical Security Parameters Used in the Module

Key Name	Description
Challenge Secret	Used in Trusted Path Authentication (Level 3) configuration only. 16 character random string generated by the HSM and output via the PED display when the user is created. It is input by the operator as the authentication data for a client application login. Stored in flash encrypted as part of the user checkword.

¹⁴ Show status is provided by invoking the “hsm showinfo” command from the administrative interface. It will display identifying information about the module such as label, serial number, firmware version, etc., and state whether the module is in FIPS-approved mode.

¹⁵ Public key value. See Table B-5 for description.

¹⁶ Use means access to key material for use in performing a cryptographic operation. The key material is never visible.

¹⁷ Transfer means moving a key using the cloning protocol from one crypto module to another.

¹⁸ The Public User has access to Public Data Objects only.



Table B-5 Keys and Critical Security Parameters Used in the Module

Key Name	Description
Random challenge	Used in Trusted Path Authentication (Level 3) configuration only. A one-time random number generated by the HSM and sent to the calling application for each login. It is combined with the input Challenge Secret to compute the one-time response that is returned to the HSM. Stored in RAM as plaintext.
Challenge Response	A 20-byte value used for authentication in the challenge response scheme. It is generated using the challenge secret and the one-time random challenge value. Stored in RAM as plaintext.
SIM authorization values	These user-supplied M of N secret values are used to authorize the insertion of a masked key blob previously extracted using the SIM II feature.
RNG Seed Value (V)	The 64 bit intermediate value of the X9.31 Annex A2.4 TDES-based PRNG algorithm. It is used as one of the initial seed values for the algorithm. It is stored in flash encrypted with the GSK.
RNG Key Value (*K)	The double-length TDES key used for the X9.31 Annex A2.4 TDES-based PRNG algorithm. It is used as one of the initial seed values for the algorithm. It is stored in flash encrypted with the GSK.
iKey Authentication Data	Used in Trusted Path Authentication (Level 3) configuration. A 48-byte random value that is generated by the module when the SO or User is created. It is written out to the serial memory device (iKey) via the Trusted Path. Authentication data may be split onto multiple iKeys using the M of N secret splitting scheme. Stored on the iKey as plaintext.
Optional PIN	An optional PIN value used for authentication along with the iKey. It must be a minimum of 4-bytes long.
Cloning Domain Vector	32-byte value that is used to control a module's ability to participate in the cloning protocol and used in the derivation of the masking key. It is either generated by the module or imprinted onto the module at the time the module is initialized. It is stored encrypted (using the SGSK) in the module. The value is output from the original module in the domain onto one or more iKeys (the M of N scheme can be used) to enable initializing additional modules into the same domain.
User Storage Key (USK)	32-byte AES key that is randomly generated for each user on a Luna PCI configured for use in the Luna® PCI Cryptographic Module for Luna® IS. This key is used to encrypt all sensitive attributes of all private objects owned by the user.
Security Officer Master Key (SMK)	The storage key for the SO; a 32-byte AES key that is randomly generated for the SO on the module. This key is used to encrypt all sensitive attributes of all private objects owned by the SO. The USK/SMK is stored encrypted using an AES key, which is the first 32 bytes of the User/SO iKey Authentication data (plus optional PIN).
Global Storage Key (GSK)	256 bit AES key that is the same for all users on a specific Luna cryptographic module. It is used to encrypt permanent parameters within the non-volatile memory area reserved for use by the module. Stored encrypted with the USK and SMK.



Table B-5 Keys and Critical Security Parameters Used in the Module

Key Name	Description
Secondary Global Storage Key (SGSK)	256 bit AES key that is the same for all users on a specific Luna cryptographic module. It is used to encrypt non-permanent parameters (parameters re-generated for every module initialization) within the non-volatile memory area reserved for use by the module. Stored encrypted using USK and SMK.
Token or Module Wrapping Key (TWK)	A 4096-bit RSA private key used in the cloning protocol. Stored in the Param area; encrypted with the GSK.
Token or Module Wrapping Certificate (TWC)	4096-bit RSA public key certificate, corresponding to the TWK, used in exchange of session encryption key as part of the handshake during the cloning protocol. Stored as plaintext in the Param area.
U Key	24-byte TDES key used in conjunction with the auth code for a firmware update to derive a key used to decrypt the firmware update image when it is loaded into the module. Used for backwards compatibility purposes with earlier firmware versions. Stored in the Param area; encrypted with the GSK.
Token or Module Variable Key (TVK)	32-byte AES key used to encrypt authentication data stored for auto-activation purposes. Stored as plaintext in dedicated non-volatile RAM.
Masking Key	AES 256-bit keys derived on the HSM individually for every user partition and for SO. SO's key is derived on the HSM at initialization time. Partitions' masking keys are derived during partitions creation. The keys are used for masking operations. Stored in flash; encrypted with the SGSK.
Manufacturer's Integrity Certificate (MIC)	4096 bit RSA public key certificate corresponding to the Manufacturer's Integrity Key (MIK) held at SafeNet. Used in verifying Hardware Origin Certificates (HOCs), which are generated in response to a customer function call to provide proof of hardware origin. Stored as plaintext in flash.
Manufacturer's Verification Key (MVK)	4096-bit Public key counterpart to the Manufacturer's Signature Key (MSK) held at SafeNet. Used to verify the digital signature on a firmware update image. Stored in flash as plaintext.
Device Authentication Key (DAK)	2048-bit RSA private key used for a specific PKI implementation requiring assurance that a key or a specific action originated within the hardware crypto module. Stored in flash encrypted with the GSK.
Device Encryption Key (DEK)	One-time AES 256 bit key used to encrypt Remote PED communications. Stored in RAM as plaintext.
Remote PED Vector (RPV)	256 bit random secret that is generated at the time the module is initialized and then used in the derivation of the DEK. Stored on iKey as plaintext.



APPENDIX C. LIST OF TERMS, ABBREVIATIONS AND ACRONYMS

Term	Definition
CA	Certification Authority
Chrysalis-ITS	Former name of SafeNet Canada, Inc.
CRT	Chinese Remainder Theorem
CSP	Critical Security Parameter
DAK	Device Authentication Key
DEK	Device Encryption Key
ECC	Elliptic Curve Cryptography
FIPS	Federal Information Processing Standard
GSK	Global Storage Key
HA	High Availability
HOC	Hardware Origin Certificate
HRNG	Hardware Random Number Generator
HSM	Hardware Security Module
KAT	Known Answer Test
MIC	Manufacturer's Integrity Certificate
MIK	Manufacturer's Integrity Key
MSK	Manufacturer's Signature Key
MVK	Manufacturer's Verification Key
PCI	Peripheral Component Interconnect
PED	PIN Entry Device
RA	Registration Authority
RPK	Remote PED Key
RPV	Remote PED Vector
SCU	Secure Capability Update
SGSK	Secondary Global Storage Key
SIM	Secure Information Management
SMK	Security Officer's Master Key
SO	Security Officer
TVK	Token or Module Variable Key
TWC	Token or Module Wrapping Certificate
TWK	Token or Module Wrapping Key
USK	User's Storage Key



- THIS PAGE LEFT BLANK INTENTIONALLY -



Document is Uncontrolled When Printed.